

## Wall Plate 4K DigitalMedia 8G+™ Receiver

- > Cost-effective DigitalMedia 8G+™ receiver
- > Connects to a DM® switcher or transmitter over a single CAT type twisted pair cable<sup>[1]</sup>
- > HDBaseT® Certified — Enables direct connection to other HDBaseT certified equipment
- > Provides one HDMI® or DVI display output<sup>[3]</sup>
- > Handles video resolutions up to 4K and Ultra HD
- > Handles 3D video and Deep Color
- > Handles Dolby® TrueHD, DTS-HD®, and uncompressed 7.1 linear PCM audio
- > HDCP compliant
- > Supports cable lengths up to 330 ft (100 m) for all resolutions up to UHD and 4K using DM Ultra cable<sup>[1]</sup>
- > Supports cable lengths up to 330 ft (100 m) for 1080p, WUXGA, and 2K using DM 8G® cable or CAT5e<sup>[1]</sup>
- > Supports cable lengths up to 230 ft (70 m) for UHD and 4K using DM 8G cable, or 165 ft (50 m) using CAT5e<sup>[1]</sup>
- > Enables device control via CEC<sup>[5]</sup>
- > Compatible with USB-EXT-DM USB over Ethernet Extenders<sup>[6]</sup>
- > Powered via the DM connection or local power pack (included)<sup>[4]</sup>
- > 1-gang wall box mount design
- > Surface mount bracket included
- > Available in white or black finish

The DM-RX1-4K-C-1G provides a simple, cost-effective interface solution for a single display device as part of a complete Crestron® DigitalMedia™ system. It functions as a DM 8G+™ receiver, providing a single HDMI® output. In addition to DM 8G+, it is also compatible with HDBaseT®, allowing it to be connected directly to an HDBaseT certified source. Its 1-gang mountable design allows the DM-RX1-4K-C-1G to be flush mounted behind a flat panel display or above a ceiling mounted projector. It can also be mounted beneath a table or attached to a suitable flat surface using the mounting bracket provided. It connects to the head end or source location using a single CAT type twisted pair cable.<sup>[1]</sup> Standard gang-box mounting allows for installation adjacent to an Ethernet jack (Crestron MP-WP183 or equivalent) for a total connectivity solution.<sup>[2]</sup>

### 4K Ultra HD

Crestron DigitalMedia continues to advance the standard for digital AV signal distribution, delivering the world's first end-to-end 4K system solution. The DM-RX1-4K-C-1G features the latest DM 8G+ technology, providing support for the transport of 4K and Ultra HD video signals. Support for 4K video also ensures support for the latest generation of computers and monitors with native resolutions beyond 1080p and WUXGA.

### DigitalMedia 8G+™

As the leader in HDMI and control system technologies, Crestron developed DigitalMedia (DM®) to deliver the first complete HD AV distribution system to take HDMI to a higher level. DigitalMedia allows virtually any mix of HDMI and other AV sources to be distributed throughout a home, office, school, or virtually any other facility. The latest generation of DM is called



Faceplate not included

DigitalMedia 8G™ (DM 8G®). Engineered for ultra high-bandwidth and ultimate scalability, DM 8G provides a true one-wire lossless transport for moving high-definition video, audio, and control signals over a choice of twisted-pair or fiber optic cable.

DM 8G over twisted-pair copper wire is called DigitalMedia 8G+ (DM 8G+). DM 8G+ handles uncompressed Full HD 1080p, Ultra HD, 2K, and 4K video signals with support for 3D, Deep Color, and HDCP. Audio capabilities include support for high-bitrate 7.1 audio formats like Dolby® TrueHD and DTS-HD Master Audio™ as well as uncompressed linear PCM. All signals are transported over a single CAT type wire, supporting 1080p, WUXGA, and 2K signals at distances up to 330 feet (100 m) using Crestron DM Ultra or DM 8G Cable, or third-party CAT5e. Higher resolutions up to UHD and 4K are supported at distances up to 330 feet (100 m) using DM Ultra Cable, 230 feet (70 m) using DM 8G Cable, or 165 feet (50 m) using CAT5e.<sup>[1]</sup>

### HDBaseT® Certified

Crestron DigitalMedia 8G+ technology is designed using HDBaseT Alliance specifications, ensuring interoperability with other HDBaseT certified products. Via its DM 8G+ input, the DM-RX1-4K-C-1G can be connected directly to an HDBaseT compliant source without requiring a DM transmitter.

### Multimedia Display Interface

A single HDMI digital AV output port is provided on the DM-RX1-4K-C-1G for connection to a display or other device. The HDMI output can also handle DVI signals using an appropriate adapter or interface cable<sup>[3]</sup>.

A single CAT type cable connects the DM-RX1-4K-C-1G to a DM switcher or transmitter, or to an HDBaseT source, transporting video, audio, control, and power signals all through one simple RJ45 connection.<sup>[1,4]</sup> Multiple DM-RX1-4K-C-1Gs may be installed to handle each display in a multiroom distribution system, all fed from a central DM-MD series switcher. Or, a

# DM-RX1-4K-C-1G Wall Plate 4K DigitalMedia 8G+™ Receiver

single DM-RX1-4K-C-1G can be fed straight from a DM 8G+ or HDBaseT transmitter, affording a simple solution for extending a computer or AV signal to a single display.

## CEC Embedded Device Control

For controlling the connected display device, the DM-RX1-4K-C-1G offers an alternative to conventional IR and RS-232 control by harnessing the CEC (Consumer Electronics Control) signal embedded in HDMI. Using CEC, many display devices can be controlled right through their HDMI connections, eliminating the need for any dedicated serial cables or IR emitters.<sup>[5]</sup>

## USB Signal Extension (optional)

DigitalMedia allows for the routing of USB signals alongside video and audio. USB signal extension is enabled on the DM-RX1-4K-C-1G by adding a [USB-EXT-DM](#) USB over Ethernet Extender Module<sup>[6]</sup>.

## Versatile Mounting Options

The DM-RX1-4K-C-1G is designed to be installed using a 3-1/2" deep 1-gang electrical box or plaster ring (not included). It can also be mounted beneath a table or attached to a suitable flat surface using the mounting bracket provided, or it can be fastened to a single rack rail in an equipment cabinet. The DM cable connects to the rear of the receiver via a shielded RJ45 DM port. The unit can be powered using the wall mount power pack (included), or via PoDM (Power over DigitalMedia) for a true one-wire solution<sup>[4]</sup>. An array of indicators is provided for easy setup and troubleshooting.

Please refer to the [DigitalMedia Resources Webpage at <http://www.crestron.com/dmresources/>](#) for additional design tools and reference documents.

## SPECIFICATIONS

### Maximum Cable Lengths

Cable Type:	DM-CBL-ULTRA DM® Ultra Cable	DM-CBL-8G DM 8G® Cable	CAT5e (or better) UTP or STP <sup>[1]</sup>
Resolution:			
1080p60 Full HD	330 ft (100 m)	330 ft (100 m)	330 ft (100 m)
1920x1200 WUXGA			
1600x1200 UXGA			
2048x1080 2K DCI		230 ft (70 m)	165 ft (50 m)
2560x1440 WQHD			
2560x1600 WQXGA			
3840x2160 Ultra HD			
4096x2160 4K DCI			

## Video

**Input Signal Types:** DM 8G+™ (DigitalMedia over one CAT type twisted pair copper wire), HDBaseT®<sup>[1]</sup>

**Output Signal Types:** HDMI®, DVI<sup>[3]</sup>

**Formats:** DM 8G+, HDBaseT, & HDMI w/Deep Color, 3D, & 4K; DVI; HDCP content protection support

**Maximum Resolutions:**

Scan Type	Maximum Resolution	Frame Rate	Color Sampling
Progressive	4096x2160 4K DCI	Up to 24 Hz	4:4:4
Progressive	3840x2160 Ultra HD	Up to 30 Hz	4:4:4
Progressive	2560x1600 WQXGA	Up to 60 Hz	4:4:4
Progressive	4096x2160 4K DCI	Up to 60 Hz	4:2:0
Progressive	3840x2160 Ultra HD	Up to 60 Hz	4:2:0
Interlaced	1920x1080 1080i30	Up to 30 Hz	4:4:4

NOTE: Common resolutions are shown; other custom resolutions are supported at pixel clock rates up to 300 MHz

## Audio

**Input Signal Types:** DM 8G+, HDBaseT

**Output Signal Type:** HDMI

**Formats:** Dolby Digital®, Dolby Digital EX, Dolby Digital Plus, Dolby® TrueHD, DTS®, DTS-ES, DTS 96/24, DTS-HD High Res, DTS-HD Master Audio™, up to 8ch PCM

## Communications

**DigitalMedia:** DM 8G+, HDCP, EDID, CEC<sup>[5]</sup>, PoDM

**HDBaseT:** HDCP, EDID, CEC<sup>[5]</sup>, PoH

**HDMI:** HDCP, EDID, CEC<sup>[5]</sup>

## Connectors – Front

**HDMI OUT:** (1) 19-pin Type A HDMI female;

HDMI digital video/audio output;

Also supports DVI<sup>[3]</sup>

## Connectors – Rear

**G:** (1) 6-32 screw, chassis ground lug

**DM IN:** (1) 8-pin RJ45 female, shielded;

DM 8G+ input, HDBaseT compliant;

PoDM and PoH PD (Powered Device) port<sup>[4]</sup>;

Connects to the DM 8G+ output of a DM switcher, transmitter, or other DM device, or to an HDBaseT device, via CAT5e, Crestron DM-CBL-8G, or Crestron DM-CBL-ULTRA cable<sup>[1]</sup>

**24VDC 0.7A:** (1) 2-pin 3.5mm detachable terminal block;

24 Volt DC power input;

PW-2407WUL power pack included

# DM-RX1-4K-C-1G Wall Plate 4K DigitalMedia 8G+™ Receiver

## Indicators

**PWR:** (1) green LED, indicates operating power supplied via PoDM, PoH, or local power pack

**VIDEO:** (1) green LED, indicates video signal presence at the HDMI output

**DM IN (rear):** (2) LEDs, green LED indicates DM link status, amber LED indicates video and HDCP signal presence

## Power Requirements

**Power Pack:** 0.75 Amps @ 24 Volts DC;  
100-240 Volts AC, 50/60 Hz power pack, model PW-2407WUL included

**Power over DM (PoDM):** PoDM PD (Powered Device), capable of being powered by a PoDM PSE (Power Sourcing Equipment), conforms to IEEE 802.3af (802.3at Type 1) Class 0 (12.95W)<sup>[7]</sup>

**Power over HDBaseT (PoH):** PoH PD (Powered Device), capable of being powered by a PoH PSE (Power Sourcing Equipment), conforms to IEEE 802.3af (802.3at Type 1) Class 3 (12.95W)<sup>[7]</sup>

Note: May be powered via power pack or PoDM/PoH, not both.

**Power Consumption:** 5.8 Watts typical;  
2.5 Watts idle

## Environmental

**Temperature:** 32° to 104°F (0° to 40°C)

**Humidity:** 10% to 90% RH (non-condensing)

**Heat Dissipation:** 19.8 BTU/hr

## Enclosure

**Construction:** Metal, black finish with white or black polycarbonate label overlay

**Flush Wall Mount:** 1-gang mountable in an extra-deep electrical box (3-1/2 inch deep minimum), requires a decorator style faceplate (not included)

**Surface Mount:** Surface mount bracket included

**Rack Mount:** Attachable to a single 19-inch EIA rack rail

## Dimensions

**Height:** 4.12 in (105 mm)

**Width:** 1.72 in (44 mm)

**Depth:** 2.35 in (60 mm)

## Weight

TBD

## MODELS & ACCESSORIES

### Available Models

**DM-RX1-4K-C-1G-B-T:** Wall Plate 4K DigitalMedia 8G+™ Receiver, Black Textured

**DM-RX1-4K-C-1G-W-T:** Wall Plate 4K DigitalMedia 8G+™ Receiver, White Textured

### Included Accessories

**PW-2407WUL:** Wall Mount Power Pack, 24VDC, 0.75A, Flying Leads, Universal (Qty. 1 included)

### Available Accessories

**DM-CBL-ULTRA-NP:** DigitalMedia™ Ultra Cable, Non-Plenum Type CMR

**DM-CBL-ULTRA-P:** DigitalMedia™ Ultra Cable, Plenum Type CMP

**DM-CBL-ULTRA-LSZH:** DigitalMedia™ Ultra Cable, Low Smoke Zero Halogen

**DM-CONN:** DigitalMedia™ Cable Connector

**DM-CBL-8G-NP:** DigitalMedia 8G™ Cable, non-plenum

**DM-CBL-8G-P:** DigitalMedia 8G™ Cable, plenum

**DM-8G-CONN:** DigitalMedia 8G™ Cable Connector

**DM-8G-CRIMP:** Crimping Tool for DM-8G-CONN

**DM-8G-CONN-WG:** DigitalMedia 8G™ Cable Connector with Wire Guide

**DM-8G-CRIMP-WG:** Crimping Tool for DM-8G-CONN-WG

**CBL Series:** Crestron® Certified Interface Cables

**MP-WP183:** Media Presentation Wall Plate - Ethernet

**USB-EXT-DM:** USB over Ethernet Extender with Routing

### Notes:

1. The maximum cable length for DigitalMedia 8G+ (DM 8G+) or HDBaseT is dependent upon the type of cable and resolution of the video signal. Refer to the "Maximum Cable Lengths" table for a detailed overview. Crestron legacy cable models **DM-CBL** DigitalMedia Cable and **DM-CBL-D** DigitalMedia D Cable support the same resolutions and cable lengths as CAT5e. Shielded cable and connectors are recommended to safeguard against unpredictable environmental electrical noise which may impact performance at resolutions above 1080p. Refer to the [Crestron DigitalMedia Design Guide, Doc. #4546](#) for complete system design guidelines. DM 8G+ is compatible with HDBaseT Alliance specifications for connecting to HDBaseT compliant equipment. All wire and cables are sold separately.
2. The DM-RX1-4K-C-1G does not include an Ethernet port. Local Ethernet connectivity for external devices requires a **MP-WP183** or equivalent Ethernet jack with a dedicated LAN connection.
3. The HDMI output requires an appropriate adapter or interface cable to accommodate a DVI signal. **CBL-HD-DVI** interface cables are available separately.
4. Receiving Power over DM (PoDM) or Power over HDBaseT (PoH) requires connection to a switcher or other equipment that has a PoDM or PoH PSE (Power Sourcing Equipment) port. Any wiring that is connected to a PoDM or PoH PSE port is for intra-building use only and should not be connected to a line that runs outside of the building in which the PSE is located.
5. Supports simple pass-through of CEC when connected directly to a **DM-TX1-4K-C-1G** transmitter. Supports full management of CEC between the locally connected HDMI device and a control system when connected to any Ethernet-enabled DM transmitter or switcher that supports CEC over HDBaseT. Refer to the spec sheet for each DM transmitter, switcher, output card, or output blade to verify "CEC" is listed under "HDBaseT" in the "Communications" section of the product's specifications.
6. USB-EXT-DM USB over Ethernet Extender Modules are sold separately. Refer to the **USB-EXT-DM** spec sheet for more information.
7. References to the IEEE 802.3af and 802.3at standards are used to demonstrate that PoDM and PoH technology is similar in function to PoE and follows the same essential specifications. The DM-RX1-4K-C-1G cannot be powered over Ethernet, and its DM IN port should not be connected directly to an Ethernet network or device.

# DM-RX1-4K-C-1G Wall Plate 4K DigitalMedia 8G+™ Receiver

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/salesreps](http://www.crestron.com/salesreps) or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: [patents.crestron.com](http://patents.crestron.com).

Crestron, the Crestron logo, DigitalMedia, DigitalMedia 8G, DigitalMedia 8G+, DM, DM 8G, and DM 8G+ are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Dolby and Dolby Digital are either trademarks or registered trademarks of Dolby Laboratories in the United States and/or other countries. DTS, DTS-HD, and DTS-HD Master Audio are either trademarks or registered trademarks of DTS, Inc. in the United States and/or other countries. HDBaseT and the HDBaseT Alliance logo are either trademarks or registered trademarks of the HDBaseT Alliance in the United States and/or other countries. HDMI and the HDMI Logo are either trademarks or registered trademarks of HDMI Licensing LLC in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2014 Crestron Electronics, Inc.