

DigitalMedia 8G+™ Transmitter 201

- > DigitalMedia 8G+™ transmitter and multimedia interface
- > Built-in 2x1 AV switcher with auto-switching and analog audio-breakaway
- > QuickSwitch HD® technology achieves fast, reliable switching
- > Connects to a DM® switcher or receiver over a single CAT type twisted pair cable^[1]
- > Supports cable lengths up to 330 ft (100 m) using DM 8G® cable or CAT5e^[1]
- > HDBaseT® Certified — Enables direct connection to other HDBaseT certified equipment
- > Provides HDMI® and RGB/component video inputs^[3]
- > Also supports DVI and DisplayPort Multimode sources^[2]
- > Handles video resolutions up to Full HD 1080p
- > Handles computer resolutions up to WUXGA
- > Handles Dolby Digital®, DTS®, and uncompressed 7.1 linear PCM audio
- > HDCP compliant
- > Includes a mini-TRS stereo analog audio input
- > Includes a local HDMI monitor output
- > Detects and reports detailed video and audio input information
- > Performs automatic AV signal format management via EDID
- > Provides a 10/100 Ethernet LAN connection
- > Enables device control via CEC and Ethernet
- > Enables USB HID signal extension for a local computer
- > Compatible with Crestron USB over Ethernet Extenders^[5]
- > Allows quick, easy setup and diagnostics
- > Low-profile surface-mount design
- > Powered via the DM connection or local power pack (included)^[4]

The DM-TX-201-C provides a simple interface for computers and high-definition AV sources as part of a complete Crestron® DigitalMedia™ system. Its low-profile, surface-mountable design makes it ideal for installation beneath a conference table, inside a lectern or equipment rack, or at virtually any other location in a boardroom, classroom, auditorium, or residence. It functions as a DM 8G+™ transmitter and switcher, providing HDMI®, VGA, and analog audio inputs along with Ethernet and USB HID ports for a total connectivity solution. In addition to DM 8G+, it is also compatible with HDBaseT®, allowing it to be connected directly to the input of an HDBaseT certified display device. It connects to the head end or display location using a single CAT type twisted pair cable.^[1]

DigitalMedia 8G+™

As the leader in HDMI and control system technologies, Crestron developed DigitalMedia (DM®) to deliver the first complete HD AV distribution system to take HDMI to a higher level. DigitalMedia allows virtually any mix of HDMI and other AV sources to be distributed throughout a home, office, school, or virtually any other facility. The latest generation of DM is called DigitalMedia 8G™ (DM 8G®). Engineered for ultra high-bandwidth and ultimate scalability, DM 8G provides a true one-wire lossless transport for moving high-definition video, audio, Ethernet, and control signals over a choice of low-cost twisted pair or fiber optic cable.



DM 8G over twisted pair copper wire is called DigitalMedia 8G+ (DM 8G+). DM 8G+ handles uncompressed Full HD 1080p video signals with support for HDCP, as well as computer signals up to WUXGA. All signals are transported over a single CAT type cable, supporting distances up to 330 feet (100 m) using Crestron [DM 8G Cable](#) or CAT5e.^[1]

HDBaseT® Certified

Crestron DigitalMedia 8G+ technology is designed using HDBaseT Alliance specifications, ensuring interoperability with other HDBaseT certified products. Via its DM 8G+ output, the DM-TX-201-C can be connected directly to an HDBaseT compliant device without requiring a DM receiver. HDBaseT connectivity through the DM-TX-201-C converges uncompressed Full HD digital video, audio, Ethernet, power, and control signals through a single CAT5e or CAT6.^[1]

Multimedia Computer/AV Interface

The DM-TX-201-C provides simple switching between two inputs. The inputs can be configured to switch automatically or be controlled through a Crestron control system. Inputs include:

- **HDMI** — Provides a digital multimedia input for mobile devices, computers, and AV sources with resolutions up to HD 1080p60 and WUXGA. Also handles DVI and DisplayPort Multimode signals using an appropriate adapter or interface cable^[2].
- **RGB** — This VGA type input handles analog RGB signals up to WUXGA 1920x1200 pixels, as well as analog video up to 1080p60^[3]. A 1/8" (3.5mm) stereo audio input is included to accommodate the analog audio signal from an unbalanced line-level source or headphone output.

Note: Audio breakaway capability enables the analog audio input to be used with either video input.

A single cable connects the DM-TX-201-C to a DM switcher or receiver, or to an HDBaseT device, transporting video, audio, control, networking, and power signals all through one simple RJ45 connection.^[1,4] Used with a single DM 8G+ Receiver/Room Controller and optional Crestron control system, the DM-TX-201-C affords a simple solution for extending a computer or AV signal to a single display. As part of a larger

DM-TX-201-C DigitalMedia 8G+™ Transmitter 201



DM-TX-201-C – Top, Front, and Bottom Views

system using a DM-MD series switcher, multiple DM-TX-201-Cs may be installed to enable the distribution of several sources at different locations to feed multiple displays throughout any room or larger facility.

In addition to its DM 8G+ output, there is also an HDMI output provided to feed a local HDMI or DVI monitor, eliminating the need for an extra outboard distribution amp or other hardware.

LAN Connectivity

Along with high-definition AV and control, DigitalMedia also integrates high-speed Ethernet networking for a total signal distribution solution. The DM-TX-201-C includes a 10/100 Ethernet port, providing a convenient LAN connection for a local network device.

USB Extender

The DM-TX-201-C also functions as a keyboard/mouse extender, allowing the connected computer (or other USB HID-compliant host) to be controlled by a mouse and/or keyboard located at a presentation lectern, conference table, or some other remote location. Expanded USB signal routing capability is available using Crestron [USB over Ethernet Extenders](#)^[5].

CEC Embedded Device Control

The primary objective of every Crestron system is to enable precisely the control desired for a seamless user experience. DigitalMedia provides an alternative to conventional IR and RS-232 device control by harnessing the

CEC (Consumer Electronics Control) signal embedded in HDMI. Through its connection to the control system, the DM-TX-201-C provides a gateway for controlling the connected source device right through the HDMI connection, potentially eliminating the need for any dedicated control wires or IR emitters.

Compact and Versatile

The DM-TX-201-C is designed to be mounted to a flat surface or placed on a shelf. It is compact enough to fit discreetly inside a presentation lectern or beneath a table, and can even be attached to a rack rail in the back of an equipment cabinet. The unit can be powered using the wall mount power pack (included), or via PoDM (Power over DigitalMedia) for a true one-wire solution^[4]. An array of indicators is provided for easy setup and troubleshooting.

A Digital Upgrade for Legacy Systems

The DM-TX-201-C also affords a perfect signal converter for integrating DigitalMedia with analog-based systems like Crestron [MPS](#), [QuickMedia](#)[®], and the CEN-RGBHV Series. A simple HD15 VGA cable connected between the output of an MPS system and the input of the DM-TX-201-C allows every RGB, component, S-Video, and composite video input on the MPS to be converted to DigitalMedia^[3]. Analog audio is converted similarly through an unbalanced stereo audio cable. The DM-TX-201-C's HDMI input may also be used to expand the input capabilities of the MPS system to handle digital AV sources.

Please refer to the [DigitalMedia Resources Webpage at http://www.crestron.com/dmresources/](http://www.crestron.com/dmresources/) for additional design tools and reference documents.

SPECIFICATIONS

Video

Switcher: 2x1 combination digital/analog switch, Crestron QuickSwitch HD[®]

Input Signal Types: HDMI[®], DVI^[2], DisplayPort Multimode^[2], RGB/VGA, component^[3], S-Video^[3], composite^[3]

Output Signal Types: DM 8G+™ (DigitalMedia™ over one CAT type twisted pair copper wire)^[1], HDBaseT[®], HDMI, DVI^[2]

Formats: DM 8G+, HDBaseT, HDMI, DVI, HDCP content protection support, RGBHV, RGBS, RGsB, YPbPr, Y/C, NTSC, PAL

Input Resolutions, HDMI & DVI, Progressive: 640x480@60Hz, 720x480@60Hz (480p), 720x576@50Hz (576p), 800x600@60Hz, 848x480@60Hz, 852x480@60Hz, 854x480@60Hz, 1024x768@60Hz, 1024x852@60Hz, 1024x1024@60Hz, 1280x720@50Hz (720p50), 1280x720@60Hz (720p60), 1280x768@60Hz, 1280x800@60Hz, 1280x960@60Hz, 1280x1024@60Hz, 1360x768@60Hz, 1365x1024@60Hz, 1366x768@60Hz, 1400x1050@60Hz, 1440x900@60Hz, 1600x900@60Hz, 1600x1200@60Hz, 1680x1050@60Hz, 1920x1080@24Hz (1080p24), 1920x1080@25Hz (1080p25), 1920x1080@50Hz (1080p50), 1920x1080@60Hz (1080p60), 1920x1200@60Hz, 2048x1080@24Hz, 2048x1152@60Hz, plus any other resolution allowed by HDMI up to 165MHz pixel clock

Input Resolutions, HDMI & DVI, Interlaced: 720x480@30Hz (480i), 720x576@25Hz (576i), 1920x1080@25Hz (1080i25), 1920x1080@30Hz

DM-TX-201-C DigitalMedia 8G+™ Transmitter 201

(1080i30), plus any other resolution allowed by HDMI up to 165MHz pixel clock

Input Resolutions, RGB: 640x480@60Hz, 720x480@60Hz (480p), 720x576@50Hz (576p), 800x600@60Hz, 848x480@60Hz, 1024x768@60Hz, 1280x720@50Hz (720p50), 1280x720@60Hz (720p60), 1280x768@60Hz, 1280x800@60Hz, 1280x960@60Hz, 1280x1024@60Hz, 1360x768@60Hz, 1366x768@60Hz, 1400x1050@60Hz, 1440x900@60Hz, 1600x1200@60Hz, 1680x1050@60Hz, 1920x1080@50Hz (1080p50), 1920x1080@60Hz (1080p60), 1920x1200@60Hz, 2048x1152@60Hz

Input Resolutions, Component^[3]: 480i, 576i, 480p, 576p, 720p50, 720p60, 1080p24, 1080i25 (1125 lines), 1080i30, 1080p30, 1080p50 (1125 lines), 1080p60

Input Resolutions, Composite and S-Video^[3]: 480i, 576i

Output Resolutions: Matched to inputs

Analog-To-Digital Conversion: 10-bit 165 MHz per each of 3 channels

Audio

Switcher: 2x1 combination digital/analog switch

Input Signal Types: HDMI, DisplayPort Multimode^[2], analog stereo

Output Signal Types: DM 8G+, HDBaseT, HDMI

Formats, HDMI: Dolby Digital®, Dolby Digital EX, DTS®, DTS-ES, DTS 96/24, up to 8ch PCM

Formats, Analog: Stereo 2-channel

Analog-To-Digital Conversion: 24-bit 48 kHz

Performance (analog): Frequency Response: 20Hz to 20kHz ±0.75dB;
S/N Ratio: >90dB, 20Hz to 20kHz A-weighted;
THD+N: <0.05% @ 1kHz;
Stereo Separation: >90dB

Communications

Ethernet: 10/100 Mbps, auto-switching, auto-negotiating, auto-discovery, full/half duplex, DHCP

USB: Supports signal extension of USB HID class devices, expandable to support virtually any USB 1.1 or 2.0 device using Crestron USB-EXT-DM USB over Ethernet Extenders^[5]

DigitalMedia: DM 8G+, HDCP, EDID, CEC, PoDM, Ethernet

HDBaseT: HDCP, EDID, PoH, Ethernet

HDMI: HDCP, EDID, CEC

NOTE: Supports management of HDCP and EDID; supports pass-through and management of CEC between HDMI source and sink, or between HDMI source and a control system

Connectors

LAN: (1) 8-wire RJ45 female, shielded; 10BaseT/100BaseTX Ethernet port

DM OUT: (1) 8-pin RJ45 female, shielded;

DM 8G+ output, HDBaseT compliant;

PoDM and PoH PD (Powered Device) port^[4];

Connects to the DM 8G+ input of a DM switcher, receiver/room controller, or other DM device, or to a HDBaseT device, via CAT5e or Crestron DM-CBL-8G cable^[1]

HDMI OUT: (1) 19-pin Type A HDMI female;

HDMI digital video/audio output;

Also supports DVI^[2]

PWR 24VDC 0.75A: (1) 2.1 x 5.5 mm DC power connector;

24 Volt DC power input;

PW-2407WU power pack included

Ground: (1) 6-32 screw, chassis ground lug

USB HID: (1) USB Type B female;

USB 2.0 device port for connection to the USB host interface of a computer or other USB HID-compliant host

HDMI IN: (1) 19-pin Type A HDMI female;

HDMI digital video/audio input;

Also supports DVI and DisplayPort Multimode^[2]

RGB IN: (1) DB15HD female;

RGB (VGA), component, S-Video, or composite video input^[3];

Formats: RGBHV, RGBS, RGsB, YPbPr, Y/C, NTSC, PAL;

Input Levels: 0.5 to 1.5 Vp-p with built-in DC restoration;

Input Impedance: 75 Ohms;

Sync Input Type: Autodetect RGBHV, RGBS, RGsB, YPbPr;

Sync Input Level: 3 to 5 Vp-p;

Sync Input Impedance: 1k Ohms

AUDIO IN: (1) 3.5mm TRS mini phone jack;

Unbalanced stereo line-level audio input;

Input Level: 2 Vrms maximum;

Input Impedance: 10k Ohms

Controls & Indicators

LAN: (2) LEDs, green LED indicates Ethernet link status, amber LED indicates Ethernet activity

DM OUT: (2) LEDs, green LED indicates DM link status, amber LED indicates video and HDCP signal presence

PWR: (1) green LED, indicates operating power supplied via PoDM, PoH, or local power pack

HDMI IN: (1) green LED, indicates HDMI input is selected

RGB IN: (1) green LED, indicates RGB input is selected

SETUP: (1) red LED and (1) miniature recessed pushbutton for Ethernet setup

RESET: (1) miniature recessed pushbutton for hardware reset

Power Requirements

Power Pack: 0.75 Amps @ 24 Volts DC;

100-240 Volts AC, 50/60 Hz power pack, model PW-2407WU included

Power over DM (PoDM): PoDM PD (Powered Device), capable of being powered by a PoDM PSE (Power Sourcing Equipment), conforms to IEEE 802.3af (802.3at Type 1) Class 3 (12.95W)^[6]

Power over HDBaseT (PoH): PoH PD (Powered Device), capable of being powered by a PoH PSE (Power Sourcing Equipment), conforms to IEEE 802.3af (802.3at Type 1) Class 3 (12.95W)^[6]

Note: May be powered via power pack or PoDM/PoH, not both.

DM-TX-201-C DigitalMedia 8G+™ Transmitter 201

Environmental

Temperature: 32° to 104°F (0° to 40°C)

Humidity: 10% to 90% RH (non-condensing)

Heat Dissipation: 30 BTU/Hr

Enclosure

Chassis: Metal, black finish, with (2) integral mounting flanges, vented sides

Mounting: Freestanding, surface mount, or attach to a single rack rail

Dimensions

Height: 6.47 in (165 mm)

Width: 7.36 in (187 mm)

Depth: 1.24 in (32 mm)

Weight

25.4 oz (721 g)

MODELS & ACCESSORIES

Available Models

DM-TX-201-C: DigitalMedia 8G+™ Transmitter 201

Included Accessories

PW-2407WU: Wall Mount Power Pack 24VDC, 0.75A, Universal (Qty. 1 included)

Available Accessories

DM-CBL-8G-NP: DigitalMedia 8G™ Cable, non-plenum

DM-CBL-8G-P: DigitalMedia 8G™ Cable, plenum

DM-8G-CONN: DigitalMedia 8G™ Cable Connector

DM-8G-CRIMP: Crimping Tool for DM-8G-CONN

DM-8G-CONN-WG: DigitalMedia 8G™ Cable Connector with Wire Guide

DM-8G-CRIMP-WG: Crimping Tool for DM-8G-CONN-WG

CBL Series: Crestron® Certified Interface Cables

MP-WP Series: Media Presentation Wall Plates

MPI-WP Series: Media Presentation Wall Plates - International Version

USB-EXT-DM: USB over Ethernet Extender with Routing

Notes:

1. For DM 8G+ or HDBaseT wiring, use Crestron [DM-CBL-8G](#) DigitalMedia 8G Cable, Crestron [DM-CBL](#) DigitalMedia Cable, Crestron [DM-CBL-D](#) DigitalMedia D Cable, or third-party CAT5e (or better) UTP or STP. Maximum wire length for DM 8G+ is 330 ft (100 m) between devices. Shielded cable and connectors are recommended to safeguard against unpredictable environmental electrical noise which may impact performance at resolutions above 1080p. Refer to the [Crestron DigitalMedia Design Guide, Doc. #4546](#) for complete system design guidelines. DM 8G+ is compatible with HDBaseT Alliance specifications for connecting to HDBaseT compliant equipment. All wire and cables are sold separately.
2. HDMI requires an appropriate adapter or interface cable to accommodate a DVI or DisplayPort Multimode signal. [CBL-HD-DVI](#) interface cables are available separately.
3. The RGB/VGA input can actually accept component, composite, and S-Video signals through an appropriate adapter (not included), or via direct interface to Crestron [MPS](#) Series products. However, input sync detection is not provided for composite or S-Video signal types through this connection.
4. Receiving Power over DM (PoDM) or Power over HDBaseT (PoH) requires connection to a switcher or other equipment that has a PoDM or PoH PSE (Power Sourcing Equipment) port. Any wiring that is connected to a PoDM or PoH PSE port is for intra-building use only and should not be connected to a line that runs outside of the building in which the PSE is located.
5. Compatible with Crestron [USB-EXT-DM-LOCAL](#) and [USB-EXT-DM-REMOTE](#) USB over Ethernet Extender modules, sold separately.
6. References to the IEEE 802.3af and 802.3at standards are used to demonstrate that PoDM and PoH technology is similar in function to PoE and follows the same essential specifications. The DM-TX-201-C cannot be powered over Ethernet, and its DM OUT port should not be connected directly to an Ethernet network or device.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Crestron, the Crestron logo, DigitalMedia, DigitalMedia 8G, DigitalMedia 8G+, DM, DM 8G, DM 8G+, QuickMedia, and QuickSwitch HD are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Dolby Digital is either a trademark or registered trademark of Dolby Laboratories in the United States and/or other countries. DTS is either a trademark or registered trademark of DTS, Inc. in the United States and/or other countries. HDBaseT and the HDBaseT Alliance logo are either trademarks or registered trademarks of the HDBaseT Alliance in the United States and/or other countries. HDMI and the HDMI Logo are either trademarks or registered trademarks of HDMI Licensing LLC in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2014 Crestron Electronics, Inc.

DM-TX-201-C DigitalMedia 8G+™ Transmitter 201

