

# ESSENCE IC8

## Essence® 8" 2-Way In-Ceiling Speakers

- > Ultimate performance 2-way in-ceiling speakers
- > 8" woven Kevlar® woofers
- > 1.1" advanced synthetic polymer dome tweeters
- > Precision 4th order crossovers
- > Cast aluminum woofer baskets
- > Extra large magnets and vented pole pieces
- > "Zero-bezel" frameless steel grilles, paintable
- > Both round and square grilles provided
- > Three-point spring-loaded toggle clamp mounting system
- > 175 Watts program power handling
- > 38Hz-20kHz frequency response
- > 8 Ohms nominal impedance
- > Sold in pairs

The product of expert Crestron® audio engineering, Essence® speakers deliver the pinnacle of performance for demanding residential installations. Select esoteric materials, top shelf components and a refined, high-end appearance underscore the meticulous design behind each model. The result is a complete line of in-wall and in-ceiling speakers worthy of a place in every room of the finest custom home.

The Essence line promises the ultimate in installed audio design, delivering simply stunning sound quality while minimizing any impact on your decor thanks to paintable zero-bezel grilles. Both round and square grilles are included. Streamlined installation of each speaker is facilitated through a three-point, spring-loaded toggle clamp mounting system optimized to minimize interference with obstructions within the ceiling space.


The Essence IC8 model provides a pair of 2-way in-ceiling speakers featuring 8 inch long-throw woven Kevlar® woofers for deep, defined low end, and large 1.1 inch advanced synthetic polymer dome tweeters for crisp, fluent highs, articulate midrange, and consistent coverage across a wider listening area. Cast aluminum woofer baskets assure pure, uncolored bass response. Offset post-mounting of the tweeters reduces midrange frequency response anomalies normally caused by interference between the woofer and the back of the tweeter. Precision 4th order crossovers utilizing the highest quality components ensure a full, rich and detailed response across the spectrum. Power handling is an impressive 175 Watts (program), with a wide frequency response from 38 Hz to 20 kHz ( $\pm 3$  dB).

### SPECIFICATIONS

#### Features & Performance

**Woofer:** 8 inch (203 mm) woven Kevlar® w/rubber surround, vented pole piece & cast aluminum basket

**Tweeter:** 1.1 inch (28 mm) advanced synthetic polymer dome, ferrofluid cooling, offset post-mounted



**Crossover:** 4th order Linkwitz-Riley  
**Crossover Frequency:** 2 kHz  
**Impedance:** 8 Ohms nominal  
**Frequency Response:** 38 Hz to 20 kHz ( $\pm 3$  dB)  
**Frequency Range:** 30 Hz to 20 kHz ( $-10$  dB)  
**Power Handling:** 175 Watts program  
**Sensitivity:** 91.5 dB @ 1W/1m

#### Connections

**Input:** (2) spring terminals;  
Maximum Wire Size: 10 AWG

#### Environmental

**Temperature:** 41° to 104°F (5° to 40°C)  
**Humidity:** 10% to 90% RH (non-condensing)  
For indoor use only

#### Construction

**Baffle:** ABS plastic, black  
**Grille:** Steel with white textured finish, paintable, magnetically-held "zero-bezel" frameless design (round and square grilles included)  
**Mounting:** Flush ceiling mount using 3 integral spring-loaded toggle clamps, 1.35 in (34 mm) maximum surface thickness, 4.75 in (121 mm) minimum mounting depth, 10.8 in (275 mm) diameter recommended cutout

#### Dimensions

**Diameter:** 11.64 in (296 mm)  
**Depth:** 4.94 in (126 mm)  
Dimensions shown are per speaker

#### Weight

7.09 lb (3.22 kg) per speaker

# ESSENCE IC8 Essence® 8" 2-Way In-Ceiling Speakers

## MODELS & ACCESSORIES

### Available Models

**ESSENCE IC8-W-T:** Essence® 8" 2-Way In-Ceiling Speakers, White Textured, Pair

### Available Accessories

- SPKA-NCTP-IC800:** New-Construction Speaker Templates
- SPKA-GRILLE-IC801:** Square Grilles (for replacement)
- SPKA-GRILLE-IC802:** Round Grilles (for replacement)
- ASPIRE IWS82:** Aspire® Dual 8" In-Wall Subwoofer

### Notes:

Crestron warrants to the original end purchaser that this Crestron Speaker Product, when purchased directly from Crestron or an authorized Crestron Dealer, will be free from defects in material and workmanship for the life of the product except for speaker grilles and outdoor rated speakers, which are warranted for five (5) years. Crestron will at its option and expense either repair the defect or replace the Speaker Product with a new or remanufactured Product or a reasonable equivalent. In cases where a new model is substituted, a modification to the mounting surface may be required. If mounting surface modification is required, Crestron assumes no responsibility or liability for such modifications.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/salesreps](http://www.crestron.com/salesreps) or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: [patents.crestron.com](http://patents.crestron.com).

Crestron, the Crestron logo, and Essence are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Kevlar is either a trademark or registered trademark of E. I. du Pont de Nemours and Company in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2014 Crestron Electronics, Inc.

