

GLPPA-KP

Keypad for GLPP Systems

- > In-wall keypad for GLPP systems
- > Seamless integration with GLPP systems
- > Set and recall scenes; control power on/off
- > Connects to the GLPP via any 2-conductor wire
- > Can use existing high- or low-voltage wiring
- > Non-polarized 2-wire communications bus
- > Available in gloss black, white and almond glossy finishes
- > Ships with rocker and a labeled 4-button layout
- > Connect up to 3 GLPPA-KP keypads to a single GLPP system

The GLPPA-KP is an in-wall keypad for **Crestron Green Light® Power Pack (GLPP)** systems used to set/recall presets and turn on/off all loads connected to a GLPP. Installation is made easy by a two-wire low-voltage bus which connects the GLPPA-KP and GLPP main unit. Available in black, white and almond, the GLPPA-KP fits almost any décor. For multi-point control in a room, up to three GLPPA-KP keypads can be connected to a single GLPP system.

Flexible Configuration

Two sets of button configurations accompany every GLPPA-KP: a rocker for turning on/off and dimming, and a set of four pre-labeled buttons for ALL ON, ALL OFF, SCENE 1, and SCENE 2. Scenes can be adjusted by any user directly from the keypad.

Easy Installation

Two flying leads connect the GLPPA-KP to the GLPP system via a non-polarized low-voltage bus. Use a choice of new or existing high-voltage (class 1) or low-voltage (class 2) wiring for quick installation.

SPECIFICATIONS

Power Requirements

1 Watt (0.05 Amps @ 24 Volts DC) supplied by GLPP over proprietary 2-wire bus

Controls

Keypad Buttons: Configurable for single rocker or 4 single-action push-buttons

Button Events: Tap, Double-tap, Hold (not all events trigger actions)

Button Caps: Includes (1) rocker and (4) small button caps with labeling

Labeling (small button caps only): Pre-labeled: ALL ON, SCENE 1, SCENE 2, ALL OFF

LED Indicators

Feedback: (1) White LEDs, illuminates when any load is above 0%

Connections

Communication Bus: (2) 18 AWG Class 2 flying leads, white with black stripe (non-polarized)



Environmental

Temperature: 32° to 113°F (0° to 45°C)

Humidity: 10% to 90% RH (non-condensing)

Enclosure

Plastic, 1-gang mountable in a standard electrical box, requires decorator style faceplate (not included)

Dimensions

Height: 4.13 in (105 mm)

Width: 1.75 in (45 mm)

Depth: 1.8 in (46 mm)

Weight

3.6 oz (103 g)

MODELS

Available Models

GLPPA-KP-A-S: In-wall Keypad for GLPP, Almond Smooth

GLPPA-KP-B-S: In-wall Keypad for GLPP, Black Smooth

GLPPA-KP-W-S: In-wall Keypad for GLPP, White Smooth

Notes:

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Crestron, the Crestron logo, and Crestron Green Light are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2014 Crestron Electronics, Inc.

GLPPA-KP Keypad for GLPP Systems

CAD DRAWINGS

