

GLS-ODT-C-NS

Dual-Technology Ceiling Mount Occupancy Sensor

- > Ceiling-mount occupancy sensor for standalone lighting systems
- > Dual-technology motion detection
- > 360 degree, 2000 square feet coverage
- > Works with GLPP, GLPAC, and GL-IPAC-SW8
- > Connect via a Versiport or digital input port
- > Discreet, low-profile appearance
- > Extremely accurate and reliable sensing
- > Fully digital circuitry for low cost and high reliability
- > Connect to a GLS-SIM for control system interface via Cresnet®

The GLS-ODT-C-NS is a low-profile, ceiling-mount occupancy sensor that delivers a powerful and cost-effective solution for reducing energy costs and enhancing the functionality of standalone lighting systems. It is designed for large areas up to 2000 square feet to detect when the room is occupied, making it great for use in large spaces such as auditoriums, warehouses, and building lobbies. Dual-technology motion sensing, available with the GLS-ODT-C-NS, affords extreme reliability for control of lighting, climate control, and other devices in the room. For power and control, the GLS-ODT-C-NS can connect directly to a [GLPP](#), [GLPAC](#), or [GL-IPAC-SW8](#). The [GLS-SIM](#) Sensor Integration Module gives the option to interface with a control system via Cresnet®.

Dual-Technology Occupancy Sensing

Achieving consistent and dependable occupancy sensing is accomplished using a combination of ultrasonic and passive infrared technologies. Ultrasonic motion detection achieves high sensitivity to small movements over a large area, while passive infrared ensures superior immunity to false triggering from vibrations, inanimate objects, or movement in an adjacent corridor. Ultrasonic motion detection can be turned on for Side A, Side B or Both sides of the occupancy sensor to avoid false occupancies facing a hallway or doorway. The GLS-ODT-C-NS allows independent sensitivity adjustment of each sensor type for optimum performance in any space.

Walk-Through Mode

The GLS-ODT-C-NS features a walk-through mode that provides specialized behavior in instances of brief occupancy, turning lights off quickly when a person enters and exits the room within a period of 90 seconds.

Versatile Installation

The GLS-ODT-C-NS was designed to achieve a discreet, nearly hidden appearance when installed on a typical drywall or droptile ceiling. Hardware is included for fast and simple mounting in a hole created by the provided cutout template or to a standard 4-inch octagon box.

Cresnet Option^[1]

Cresnet provides a simpler solution for configuring and wiring sensors as part of any complete Crestron® system. Cresnet is the communications backbone for Crestron lighting dimmers, keypads, touch screens, shades, thermostats, and many other devices. This flexible 4-wire bus provides data communications and 24 Volts DC power for all of the devices on the Cresnet network. Using the optional GLS-SIM Sensor Integration Module, the GLS-ODT-C-NS becomes a full-featured Cresnet device, streamlining the total lighting system.



IR Remote

A variety of parameters can be set for the GLS-ODT-C-NS by using the [GLS-REMOTE-ODT/OIR](#) remote (sold separately). This IR remote eliminates the need for a ladder to commission or set up any system. The installer can simply stand underneath the sensor and use the remote to complete setup functions and fine tune sensor settings after installation.

SPECIFICATIONS

Sensing

Sensor Technology: Passive Infrared and Ultrasonic (40 kHz)

Coverage Area: 2000 sq. ft.

Coverage Pattern: 360 degrees

LED Indicators

IR: (1) Red LED, PIR detection

Ultrasonic: (1) Green LED, Ultra Sonic detection

IR Remote (sold separately)

Parameters and settings available through IR remote:

Separate Occupancy and Vacancy sensitivity settings;

Timeout (30s, 2m, 5m, 10m, 15m, 30m);

Walk-Through mode "Short Timeout" (Enable/Disable);

LEDs (Enable/Disable);

PIR Sensitivity (High, Med, Low, OFF), with the option to set separate occupancy and vacancy settings;

US Sensitivity (High, Med, Low, OFF), with the option to set separate occupancy and vacancy settings;

US detection (Side A only, Side B only, Both);

Factory Reset;

Force Vacancy;

4 Custom buttons (for future additional features)

Connections

(1) 5-pin 3.5mm detachable terminal block; 16 AWG maximum wire width supported, includes the following terminals:

+24V: DC power input

OCC: Occupancy sensor control signal output; provides 24 Volts DC high logic signal when occupancy is detected (both PIR and US must sense occupancy to provide 24 V signal, if room is transitioning from a vacant to occupied state; after initial occupancy is detected, either PIR or US detection will trigger the 24 V signal to maintain the occupied state);

Short circuit protected;

Connects to a GLS-SIM Integration Module (sold separately) on any Crestron® control system

NC: Unused

G: Ground

IR: IR single direction, transmits information read from remote by IR receiver on sensor

Environmental

Temperature: 32° to 104°F (0° to 40°C)

Humidity: 10% to 90% RH (non-condensing)

Power Requirements

Current Consumption: 45 mA @ 24 Volts DC

Cresnet® Power Usage: 1 Watt

Enclosure

Housing: Plastic, white

Mounting: Mounts to a 4" (102 mm) octagon box or ~3-1/2" (88 mm) diameter hole created by provided cutout template. Includes mounting screws and integral toggle clamps. A 1-1/2" (38 mm) minimum mounting depth is recommended.

Dimensions

Diameter: 4.80 in (122 mm)

Depth: 2.30 in (59 mm) overall, 0.97 in (25 mm) exposed

Weight

5.1 oz (144 g)

Standards & Certifications

UL60730-1, FCC, CE, C-Tick, IC, Plenum Rated, California Title 24 Code

MODELS & ACCESSORIES

Available Models

GLS-ODT-C-NS: Dual-Technology Ceiling Mount Occupancy Sensor

Available Accessories

GLS-REMOTE-ODT/OIR: IR Remote for GLS Occupancy Sensors

GLS-SIM: Sensor Integration Module

Notes:

1. The GLS-ODT-C-NS requires a GLS-SIM for Cresnet.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Crestron, the Crestron logo, Cresnet, and Crestron Green Light are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2014 Crestron Electronics, Inc.

GLS-ODT-C-NS

Dual-Technology Ceiling Mount Occupancy Sensor

CAD DRAWING

