

HD-DA-2

1-to-2 HDMI® Distribution Amplifier & Audio Converter

- > Provides a high-performance one in, two out HDMI® signal splitter
- > Enables extracting analog and SPDIF audio signals from the HDMI source
- > Enables embedding SPDIF audio (coax or optical) onto the HDMI outputs
- > Allows merging DVI and SPDIF audio sources into one HDMI signal
- > Supports HD 1080p w/Deep Color, 3D, and 7.1 linear PCM or high-bitrate encoded audio
- > Compatible with DVI and DisplayPort Multimode^[1]
- > Allows versatile configuration of EDID and HDCP key handling
- > Includes HDMI signal and HDCP status indicators
- > No programming or control system required
- > Ideal for portable or fixed installation use

Do you need to feed two video displays from one HDMI® source? Or, split an HDMI signal between a display and a surround sound processor? Need to break out the HDMI audio signal and convert it to SPDIF or analog? Or, merge separate digital audio and video sources into one HDMI stream? Not a problem—just use the HD-DA-2.

The HD-DA-2 from Crestron® provides a versatile HD AV signal problem solver with high-performance specs and set-and-forget simplicity.

HDMI Signal Splitter

As an HDMI distribution amp, the HD-DA-2 lets you easily share one HDMI signal between two display devices, or split that signal to feed one display and a separate audio processor. Ideal for use with Blu-ray Disc® and multimedia computer sources, the HD-DA-2 supports high-definition video up to 1080p60 with Deep Color and 3D, as well as high-resolution computer signals up to 1920x1200. It also handles high-bitrate 7.1 surround sound audio formats like Dolby® TrueHD and DTS-HD Master Audio™.

HDMI Audio Extractor

In addition to its two HDMI outputs, the HD-DA-2 also includes a SPDIF coaxial digital audio output and a stereo analog audio output, allowing the audio signal to be extracted from the HDMI source and converted to feed a legacy audio device. The SPDIF output supports surround sound signals up to 6.1, while the analog output handles stereo 2-channel signals.

HDMI Audio Embedder

The HD-DA-2 also provides SPDIF coaxial and optical digital audio inputs, either of which may be selected as the audio source in place of the incoming HDMI audio signal. This allows any HDMI video signal to be merged with an alternate audio source, effectively letting you generate a new HDMI AV signal containing your choice of audio and video sources. The HDMI input can even accept the signal from a DVI digital video source^[1], allowing separate DVI and SPDIF signals to be merged into one HDMI signal, perfect for integrating an older digital AV source or computer into a modern HDMI based system.



1-to-4 Audio Distribution

All of the outputs on the HD-DA-2 can be used simultaneously to feed up to four separate devices. The surround sound format for all outputs is simply limited to the best common format supported by the selected input and outputs. For instance, if you are using the analog output, which only supports stereo 2-channel signals, then the HDMI and SPDIF outputs will be limited to 2-channel PCM. If you'd like to distribute Dolby Digital® or DTS® 5.1 surround sound via the SPDIF output, then the HDMI outputs will be limited to 5.1 as well and the analog output will be disabled entirely. Eight-channel PCM and high-bitrate 7.1 formats like Dolby TrueHD and DTS-HD Master Audio can only be handled by HDMI, so naturally all the other inputs and outputs on the HD-DA-2 must be disabled in order to pass the highest quality formats.

Reliable Performance with Simple Setup

Configuring the HD-DA-2 for each application requires just a quick setting of its DIP switches. The switches provide a simple yet versatile means for selecting the audio input source, configuring EDID, and choosing which audio formats to allow.

Embedded in every HDMI signal, EDID (Extended Display Identification Data) allows a display or audio processor to inform the upstream source about its format and resolution capabilities, enabling the source to configure itself to deliver an optimum signal to the downstream device. The HD-DA-2 provides extra measures to ensure optimum results when distributing HDMI to multiple destinations, letting the installer select which output device provides the EDID, or letting the HD-DA-2 determine the best common resolution and format that both devices can support. It also allows the audio EDID to be controlled independent of the video, even letting the installer manually limit the audio format based on the inputs and outputs in use.

Reliability is further enhanced by allowing the installer to limit the number of HDCP (High-bandwidth Digital Content Protection) keys to match the capabilities of the source, ensuring the core system remains functional in the event too many devices get connected.

HD-DA-2 1-to-2 HDMI® Distribution Amplifier & Audio Converter

SPECIFICATIONS

Video

Input Signal Types: HDMI, DVI^[1], DisplayPort Multimode^[1]
Output Signal Types: HDMI, DVI^[1]
Formats: HDMI w/Deep Color & 3D, DVI, HDCP content protection support
Input Resolutions, Progressive: 640x480@60Hz, 720x480@60Hz (480p), 720x576@50Hz (576p), 800x600@60Hz, 848x480@60Hz, 852x480@60Hz, 854x480@60Hz, 1024x768@60Hz, 1024x852@60Hz, 1024x1024@60Hz, 1280x720@50Hz (720p50), 1280x720@60Hz (720p60), 1280x768@60Hz, 1280x800@60Hz, 1280x960@60Hz, 1280x1024@60Hz, 1360x768@60Hz, 1365x1024@60Hz, 1366x768@60Hz, 1400x1050@60Hz, 1440x900@60Hz, 1600x900@60Hz, 1600x1200@60Hz, 1680x1050@60Hz, 1920x1080@24Hz (1080p24), 1920x1080@25Hz (1080p25), 1920x1080@50Hz (1080p50), 1920x1080@60Hz (1080p60), 1920x1200@60Hz, 2048x1080@24Hz, 2048x1152@60Hz, plus any other resolution allowed by HDMI up to 165MHz pixel clock
Input Resolutions, Interlaced: 720x480@30Hz (480i), 720x576@25Hz (576i), 1920x1080@25Hz (1080i25), 1920x1080@30Hz (1080i30), plus any other resolution allowed by HDMI up to 165MHz pixel clock
Output Resolutions: Matched to inputs

Audio

Switcher: 3x1 digital switch
Input Signal Types: HDMI, DisplayPort Multimode^[1], SPDIF coaxial, SPDIF optical (TOSLINK)
Output Signal Types: HDMI, SPDIF coaxial, analog 2-channel
Formats, HDMI & SPDIF: Dolby Digital®, Dolby Digital EX, DTS®, DTS-ES, DTS 96/24, 2ch PCM
Formats, HDMI only: Dolby Digital Plus, Dolby® TrueHD, DTS-HD High Res, DTS-HD Master Audio™, Up to 8ch PCM
Formats, Analog: Stereo 2-channel
Digital-To-Analog Conversion: 24-bit 48 kHz
Performance (analog): Frequency Response: 20Hz to 20kHz ±1dB
S/N Ratio: >70dB, 20Hz to 20kHz A-weighted
THD+N: <0.2% @ 1kHz
Stereo Separation: >60dB

Communications

USB: For console, USB 2.0 client
HDMI: Passes CEC (between HDMI IN & HDMI OUT 1 only), provides EDID and HDCP key management

Connectors - Top

AUDIO IN, OPTICAL: (1) JIS F05 female (TOSLINK) optical fiber connector; S/PDIF optical digital audio input
AUDIO IN, SPDIF: (1) RCA female; S/PDIF coaxial digital audio input; Input Impedance: 75 Ohms

AUDIO OUT, SPDIF: (1) RCA female; S/PDIF coaxial digital audio output; Output Impedance: 75 Ohms

AUDIO OUT, R – L: (2) RCA female; Unbalanced stereo line-level audio output; Maximum Output Level: 2 Vrms; Output Impedance: 100 Ohms nominal

Connectors - Bottom

HDMI IN: (1) 19-pin Type A HDMI female; HDMI digital video/audio input; Also supports DVI and DisplayPort Multimode^[1]

HDMI OUT 1 – 2: (2) 19-pin Type A HDMI female; HDMI digital video/audio outputs; Also supports DVI^[1]

COMPUTER: (1) USB Type B female, USB 2.0 computer console port

PWR 24 VDC 0.21A: (1) 2.1 x 5.5 mm DC power connector; 24 Volt DC power input, PW-2407WU power pack included

Ground: (1) 6-32 screw, chassis ground lug

Controls & Indicators

CONFIG, AUDIO: (8) Toggle DIP Switches; configure audio source, audio format, audio EDID, and video EDID

CONFIG, HDCP: (1) 16-position rotary DIP Switch, selects number of HDCP keys

HDMI IN: (1) red/green dual-color LED, green indicates valid HDMI input signal presence, red indicates HDMI source requires authentication

HDMI OUT 1 – 2: (2) red/green dual-color LEDs, green indicates presence of a non-HDCP signal, red indicates presence of an HDCP signal

PWR 24 VDC 0.21A: (1) green LED, indicates 24 Volts DC power supplied from power pack

Power Requirements

Power Pack: 0.21 Amps @ 24 Volts DC; 100-240 Volts AC, 50/60 Hz power pack, model PW-2407WU included

Environmental

Temperature: 32° to 104°F (0° to 40°C)
Humidity: 10% to 90% RH (non-condensing)
Heat Dissipation: 18 BTU/Hr

Enclosure

Chassis: Metal, black finish, with (2) integral mounting flanges
Mounting: Freestanding, surface mount, or attach to a single rack rail

Dimensions

Height: 4.53 in (115 mm)
Width: 7.21 in (183 mm)
Depth: 1.24 in (32 mm)

HD-DA-2 1-to-2 HDMI® Distribution Amplifier & Audio Converter

Weight

1.1 lb (0.50 kg)

MODELS & ACCESSORIES

Available Models

HD-DA-2: 1-to-2 HDMI® Distribution Amplifier & Audio Converter

Included Accessories

PW-2407WU: Wall Mount Power Pack 24VDC, 0.75A, Universal (Qty. 1 included)

Available Accessories

CBL-HD-LOCK: Locking High-Speed HDMI® Cable

CBL-HD: Crestron® Certified HDMI® Interface Cable

CBL-HD-DVI: Crestron® Certified HDMI® to DVI Interface Cable

CBL-RCA: Crestron® Certified RCA S/PDIF Audio Interface Cable

CBL-RCA2: Crestron® Certified RCA Stereo Audio Interface Cable

MP-WP140: Media Presentation Wall Plate - DVI-I w/Mini-TRS Stereo Audio

MP-WP150: Media Presentation Wall Plate - HDMI® w/Mini-TRS Stereo Audio

MP-WP152: Media Presentation Wall Plate - HDMI®

MPI-WP150: Media Presentation Wall Plate - International Version - HDMI® w/Mini-TRS Stereo Audio

Notes:

1. HDMI IN requires an appropriate adapter or interface cable to accommodate a DVI or DisplayPort Multimode signal. HDMI OUT requires an appropriate adapter or interface cable to accommodate a DVI signal. [CBL-HD-DVI](#) interface cables available separately.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Crestron and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Blu-ray Disc is either a trademark or registered trademark of the Blu-ray Disc Association in the United States and/or other countries. Dolby and Dolby Digital are either trademarks or registered trademarks of Dolby Laboratories in the United States and/or other countries. DTS and DTS-HD Master Audio are either trademarks or registered trademarks of DTS, Inc in the United States and/or other countries. HDMI and the HDMI Logo are either trademarks or registered trademarks of HDMI Licensing LLC in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2013 Crestron Electronics, Inc.

HD-DA-2 1-to-2 HDMI® Distribution Amplifier & Audio Converter

