

TPMC-4SM-FD

4.3" Touch Screen w/Full Duplex Audio & Room Scheduling

- > Modern, contoured appearance
- > Thin profile and small footprint
- > Affordable and easy to install
- > 4.3" widescreen active-matrix color touch screen
- > 800 x 480 WVGA display resolution
- > Smart Graphics™ support
- > High-performance H.264 streaming video
- > Rava™ SIP Intercom and phone technology
- > Full-duplex voice communication
- > Customizable audio feedback
- > Built-in microphone and speaker
- > Built-in proximity sensor
- > 10 optional "hard key" pushbuttons
- > Dual-color button backlighting and feedback
- > Custom engravable button text
- > Fusion RV® room scheduling mode
- > Room occupancy sensor option^[2]
- > Single-wire Ethernet connectivity
- > PoE network powered
- > Surface mountable over a 2" square hole or wall box^[1]
- > Available with black or white smooth finish

With its clean, contoured appearance, the TPMC-4SM-FD Touch Screen from Crestron® makes an elegant statement in any environment. Perfectly at home in the most modern office building, hotel, or residence, its high-tech good looks underline its power for simplifying everyday tasks and functions throughout any facility, all in a very affordable device that's versatile and easy to install. It mounts over a standard electrical box or small hole on a wall or similar surface^[1], achieving a thin profile and small footprint.

The TPMC-4SM-FD provides a customizable touch screen controller featuring Smart Graphics™, H.264 streaming video, audio feedback, and Rava™ SIP Intercom, cohesively merged into one seamless user interface. Additional features include dual-color backlit buttons, a built-in proximity sensor, PoE network power, occupancy sensor inputs, and out-of-the-box room scheduling capability for use with Crestron Fusion RV® Remote Asset Management Software.

Advanced Touch Screen Control

A Crestron touch screen offers an ideal user-interface for controlling all the technology in your home, boardroom, classroom, courtroom, or command center. Touch screens do away with piles of remote controls, cluttered wall switches, and cryptic computer screens, simplifying and enhancing the way you use technology. Crestron touch screens are fully-customizable for controlling audio, video, lighting, shades, HVAC, security, and other systems — with easy-to-use controls and icons, true feedback and real-time status display, live streaming video, and advanced navigation of digital media servers, tuners, and other devices.



Smart Graphics™

Crestron touch screens use Smart Graphics to deliver the ultimate user experience *and* the ultimate value by enabling the creation of dynamically rich user interfaces with incredible efficiency and unparalleled functionality. Using Smart Graphics, programmers can swiftly integrate fluid gesture-driven controls, animated feedback, metadata, and video for a deeply engaging and ultra-intuitive touch screen experience.

Crestron Smart Graphics include the following enhancements:

- Cool-looking graphical buttons, sliders, knobs, and gauges are intuitive and fun to use.
- Kinetic effects enhance the feeling of realism with lists and toolbars that scroll with momentum at the flick of a fingertip.
- Drag-and-drop objects snap into place offering an easy way to switch sources.
- Dashboard widgets personalize the touch screen with clocks, weather, news, and other information.
- Customizable themes allow a completely different look and feel for every user, event, or season.
- Fully-developed SmartObjects™ enable sophisticated control over complex devices with minimal programming.

Dual-Color Backlit Buttons

The TPMC-4SM-FD comes standard with 10 programmable "hard key" pushbuttons for quick access to commonly used functions. Each button features a translucent button cap with a choice of red or green LED backlighting. The backlighting is fully dimmable, either globally or separately for the left side and right side. Alternately, each button LED can be programmed to provide discrete feedback, affording clear indication of the status of each individual button.

TPMC-4SM-FD 4.3" Touch Screen w/Full Duplex Audio & Room Scheduling

The TPMC-4SM-FD comes standard with its buttons pre-labeled for room scheduling functions. Customized labeling can be attained using Crestron Engraver software. Or, for a clean appearance, either column of buttons may be removed and covered using the no-button covers provided.

Room Scheduling Mode

The TPMC-4SM-FD works directly with Crestron Fusion RV Remote Asset Management Software to provide a powerful room scheduling solution. Installed outside the entrance to every meeting room, the TPMC-4SM-FD provides an immediate view of each room's availability, with the ability to look up the calendar for any room on the network, and even book the room right on-the-spot. The dual-color buttons give a clear indication of a room's status at-a-glance, lighting green when the room is available and red when it is in use. The touch screen's contoured shape assures that the buttons remains clearly visible at a distance to either side — even when mounted in a narrow hallway.

Occupancy Sensing

Crestron [GLS-series](#) room occupancy sensors can be connected directly to the TPMC-4SM-FD to allow automation of the room's lighting, climate control, and other devices. In Room Scheduling Mode, the sensors allow Fusion RV to detect when no one has shown up for a scheduled meeting, so even if the meeting is not cancelled or rescheduled by its host, the calendar can be updated automatically to make the room available to other users.

Proximity Sensor

The TPMC-4SM-FD senses as you approach it, waking its display automatically without having to touch the screen so it's always ready for use.

Streaming Video

High-performance streaming video capability makes it possible to view security cameras and other video sources over the network right on the touch screen. Native support for H.264 and MJPEG formats allows the TPMC-4SM-FD to display live video images from IP cameras and servers such as the Crestron [CEN-NVS200](#) Network Video Streamer^[2].

Rava™ SIP Intercom

Rava SIP Intercom Technology enables hands-free VoIP communication between any two Rava-enabled Crestron touch screens. Rava works over Ethernet, supporting 2-way intercom, video intercom^[3], paging, and room monitoring without any special wiring. VoIP phone capability is also possible through integration with an SIP-compatible IP phone system or SIP server, allowing hands-free telephone functionality complete with speed-dialing, caller ID, custom ringers, and other enhancements. Built-in echo cancellation affords true-duplex performance for clear, seamless voice communication using the TPMC-4SM-FD's integrated microphone and speakers.

Audio Feedback

Customized audio files can be loaded on the TPMC-4SM-FD to add another dimension to its touch screen graphics using personalized sounds, button feedback, and voice prompts.

Single-Wire Connectivity

A simple Ethernet LAN connection is all that is required to wire the TPMC-4SM-FD, containing all control, video, intercom, and power signals within a single wire.

Power over Ethernet

Using PoE technology, the TPMC-4SM-FD gets its operating power right through the LAN wiring. PoE (Power over Ethernet) eliminates the need for a local power supply or any dedicated power wiring. A PoE Injector ([PWE-4803RU](#)^[2]) simply connects inline with the LAN cable at any convenient location. Crestron PoE switches ([CEN-SW-POE-5](#), [CEN-SW-POE-16](#), or [CEN-SW-POE-24](#)^[2]) may also be used to provide a total networking solution with built-in PoE.

Simple, Versatile Mounting

The TPMC-4SM-FD installs easily using a 1-gang or 2-gang electrical box or a 2-gang UK electrical box. It can also be attached directly to drwall and other surfaces over the front of a roughly 2 inch square hole. It requires just 1/2-inch mounting depth while protruding less than an inch from the wall surface.^[1]

SPECIFICATIONS

Touch Screen Display

Display Type: TFT Active matrix color LCD
Size: 4.3 inch (109 mm) diagonal
Aspect Ratio: 16:9 WVGA
Resolution: 800 x 480 pixels
Brightness: 270 nits (cd/m²)
Contrast: 300:1
Color Depth: 16-bit, 64k colors
Illumination: Backlit LED
Viewing Angle: ±80° horizontal, ±80° vertical
Touch Screen: Resistive membrane

Buttons

Hard Keys: (10) Optional programmable pushbuttons, translucent backlit
Feedback/Backlight: (1) red and (1) green LED per hard key, programmable for feedback and backlighting
Reset: (1) Recessed pushbutton behind pinhole for hardware reset

Proximity Sensor

Type: Active infrared beam and receiver
Range: 3-4 feet
Wakes the touch screen and backlight

Memory

SDRAM: 256 MB
Flash: 2 GB
Maximum Project Size: 60 MB

TPMC-4SM-FD 4.3" Touch Screen w/Full Duplex Audio & Room Scheduling

Graphics Engine

Supports Smart Graphics™ or “traditional” GUI projects

Communications

Ethernet: 10/100 Mbps, auto-switching, auto-negotiating, auto-discovery, full/half duplex, DHCP, IEEE 802.3af and 802.3at compliant

Video

Streaming Formats: H.264 (MPEG-4 part 10 AVC), MJPEG

Audio

Features: Built-in microphone and speaker, Rava™ SIP Intercom, Crestron IP Intercom, 60 dB echo cancellation

Amplification: Mono, 0.5 Watts

Audio Feedback Formats: MP3 using Smart Graphics, WAV using “traditional” graphics

Connectors

LAN PoE: (1) 8-wire RJ45 with 2 LED indicators; 10Base-T/100Base-TX Ethernet port, Power over Ethernet compliant; Green and yellow LEDs indicate Ethernet port status

Occupancy Sensor Input: (4) captive screw terminals comprising (2) voltage sensing inputs (referenced to GND) with 24 Volt DC power output; Input Voltage Range: 0-30 Volts DC; Sensing Threshold: ≥ 4.5 Volts DC active, ≤ 1 Volt DC inactive; Maximum DC Load: 4 Watts @ 24 Volts DC, provides operating power for up to (4) Crestron GLS Series occupancy sensors

Power Requirements

Power over Ethernet: IEEE 802.3af (802.3at Type 1) Class 3 PoE Powered Device

Environmental

Temperature: 32° to 104°F (0° to 40°C)

Humidity: 10% to 90% RH (non-condensing)

Heat Dissipation: 14 BTU/Hr

Enclosure

Construction: Plastic, black or white, smooth finish

Front Bezel: Plastic, hard buttons installed with pre-labeled button covers, custom engraving sold separately, “no-button” covers also included

Mounting: Surface mount^[1], or mounts to a vertically-oriented 1-gang or 2-gang electrical box^[1], a horizontally-oriented 1-gang electrical box^[1], or a 2-Gang UK (BS 4662) electrical box; choice of standard or security screws provided

Dimensions

Height: 4.00 in (102 mm)

Width: 6.20 in (158 mm)

Depth: 1.28 in (33 mm)

Weight

9.5 oz (268 g)

MODELS & ACCESSORIES

Available Models

TPMC-4SM-FD-B-S: 4.3" Touch Screen w/Full Duplex Audio & Room Scheduling, Black Smooth

TPMC-4SM-FD-W-S: 4.3" Touch Screen w/Full Duplex Audio & Room Scheduling, White Smooth

Available Accessories

4SM-BTNO: Engravable Button Covers w/Custom Engraving, Set of 2

PWE-4803RU: PoE Injector

CEN-SW-POE-5: 5-Port PoE Switch

CEN-SWPOE-16: 16-Port Managed PoE Switch

CEN-SWPOE-24: 24-Port Managed PoE Switch

GLS-ODT Series: Crestron Green Light™ Dual-Technology Occupancy Sensors

GLS-OIR Series: Crestron Green Light™ Passive Infrared Occupancy Sensors

CEN-NVS200: Network Video Streamer

SW-VMK-WIN: TouchPoint® Virtual Mouse & Keyboard Software for Windows®

Notes:

1. Requires a minimum cut-out or electrical box opening of 1.7" high x 2.0" wide. See specifications for electrical box compatibility.
2. Item(s) sold separately.
3. H.264 compatible IP camera required.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Crestron, the Crestron logo, Fusion RV, Rava, Smart Graphics, SmartObjects, and TouchPoint are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Windows is either a trademark or registered trademark of Microsoft Corporation in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2013 Crestron Electronics, Inc.

TPMC-4SM-FD

4.3" Touch Screen w/Full Duplex Audio & Room Scheduling

