

## Wall Mount Docking Station for TPMC-8X Series

The TPMC-8X-DSW Wall Mount Docking Station facilitates charging of an Isys® TPMC-8X-GA WiFi Touch Screen while simultaneously enabling fully wired touch screen operation.

### Secure Wall Mount Dock

While docked, the touch screen is secured in place by an electronic latch. The touch screen lays flush within the docking station providing a refined appearance while prohibiting prying fingers or an accidental bump from dislodging it. When released, the mechanism gently extends the touch screen outward, ready to be disengaged for portable use.

Pass code protection can be employed on the touch screen to prevent unauthorized removal from the docking station. All functions of the docking station can also be controlled programmatically from the control system via Ethernet, and through [Crestron RoomView®](#) or [Fusion RV™](#) software. A hardware key is provided to release the touch screen from the docking station in the case of a power failure.

### High-Speed Connectivity

On the rear of the TPMC-8X-DSW, a 10/100 Ethernet port provides for direct connection to a wired LAN, allowing wired operation of the touch screen while docked in the absence of a wireless connection. Two (2) USB ports are included to support a wired mouse and keyboard (not included).

### Audio Output

A balanced line output allows for connection to [Sonnex™](#), [Adagio®](#), and other multi-room audio distribution systems using CAT5 or conventional wiring. Through this connection, streaming audio content playing on the touch screen can be shared with listeners throughout the home or office.

### Multi-Battery Charger

The TPMC-8X-DSW not only charges the touch screen's internal battery, it can charge an optional external battery pack as well. In fact, it can charge one external battery pack attached to the touch screen while simultaneously charging a second spare external battery pack placed in its own charging slot within the docking bay. The spare battery pack can even be left in place to charge while the touch screen is removed, keeping one battery pack charging at all times.<sup>[1]</sup>

**IMPORTANT:** *This spec sheet is for TPMC-8X-DSW, Material # 6504859, which is compatible with the TPMC-8X-GA, as well as with previous model TPMC-8X touch screens. Owners of an older model TPMC-8X-DSW who wish to use it with a TPMC-8X-GA must contact Crestron Customer Support to acquire the TPMC-8X-DSW BEZEL CONVERSION KIT, Material # 6505136.*



Touch screen not included.

## SPECIFICATIONS

### Connectors

**PWR:** (1) 2-pin 3.5mm detachable terminal block;  
24 Volt DC power input;  
Wire Size: 18 AWG maximum

**LAN:** 8-wire RJ45, 10Base-T/100Base-TX Ethernet port

**USB:** (2) USB Type A female;  
USB 2.0 ports for keyboard, mouse, and storage devices

**AUDIO:** (1) 5-pin 3.5mm detachable terminal block;  
Balanced/unbalanced stereo line-level audio output

**Docking Port:** Mates with the touch screen while docked<sup>[1]</sup>

### Controls & Indicators

**Power/Suspend:** (1) Pushbutton, activates the POWER/SUSPEND function on the touch screen<sup>[1]</sup>

**Charging Status:** (1) Dual-color LED, orange indicates an external battery pack is charging in the spare battery slot, green indicates battery is fully charged<sup>[1]</sup>

**Docked Sensor:** (1) Sensor integrated into docking station bezel, senses when a touch screen is docked

**Audio Output:** (1) 2-position switch (behind front bezel), enables/disables AUDIO connector

**LAN:** (2) LEDs on side panel LAN port, green indicates Ethernet link status, amber indicates Ethernet activity

### Power Requirements

75 Watts (3.13 Amps) @ 24 Volts DC;  
Requires dedicated CNPWS-75 or dedicated channel of C2N-SPWS300, both sold separately

# TPMC-8X-DSW Wall Mount Docking Station for TPMC-8X Series

## Environmental

---

**Temperature:** 41° to 122°F (5° to 50°C)

**Humidity:** 10% to 90% RH (non-condensing)

## Enclosure

---

**Chassis:** Metal, flush-mountable (all mounting accessories sold separately)

**Faceplate:** Plastic, color-matched to touch screen

## Dimensions

---

**Height:** 10.16 in (258 mm)

**Width:** 11.74 in (298 mm)

**Depth:** 3.67 in (93 mm)

## Weight

---

4.7 lb (2.13 kg)

## MODELS & ACCESSORIES

### Available Models

---

**TPMC-8X-DSW:** Wall Mount Docking Station for TPMC-8X or TPMC-8X-GA

### Available Accessories

---

**BB-8X-DSW:** Pre-Construction Wall Mount Back Box

**PMK-8X-DSW:** Pre-Construction Wall Mount Kit

**MMK-8X-DSW:** Mud Ring

**TMK-8X-DSW:** Trim Ring

**WMKM-8X-DSW:** Post-Construction Wall Mount Kit with Mud Ring

**WMKT-8X-DSW:** Lectern or Post-Construction Wall Mount Kit with Trim Ring

**CNPWS-75:** Cresnet Power Supply, 75 Watts

**CNPWSI-75:** Cresnet Power Supply, 75 Watts - International Version, 230V

### Notes:

1. TPMC-8X-GA touch screen and all battery packs sold separately.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/salesreps](http://www.crestron.com/salesreps) or by calling 800-237-2041.

Specifications subject to change without notice. Crestron is not responsible for errors in typography or photography.

Adagio, Crestron, Crestron RoomView, Fusion RV, Isys, Sonnex, and the Crestron logo are trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and other countries. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. ©2011 Crestron Electronics, Inc.

# TPMC-8X-DSW Wall Mount Docking Station for TPMC-8X Series

