

TSS-752

7" Room Scheduling Touch Screen

- > Room scheduling touch screen
- > For use with Crestron Fusion RV® software
- > Intuitive on-screen scheduling interface
- > 7" widescreen active-matrix color display
- > Capacitive touch screen technology
- > Smart Graphics™ support [3]
- > Crestron Fusion® multi-language support
- > Occupancy sensor support via control system
- > High-performance H.264 streaming video [4]
- > Rava™ SIP intercom and phone technology [4]
- > Customizable audio feedback [4]
- > Built-in microphone and speaker [4]
- > Side-mounted multi-color room status indicators
- > 5 soft-touch capacitive buttons
- > Single-wire Ethernet connectivity
- > PoE network powered
- > Standard electrical wall box mounting
- > Multi-surface mounting option available [1]
- > Clean, modern appearance
- > Available with black or white smooth finish

Crestron® Room Scheduling Touch Screens provide an invaluable productivity tool for organizations with multiple conference rooms and meeting spaces. Mounted on the wall outside each room, they allow anyone to see at a glance if a room is available or in use, and view details about the current meeting. A swipe of the finger across the color touch screen reveals the room's entire schedule. Upcoming meetings and open time slots are clearly displayed on a scrolling calendar ribbon, and users can even reserve a room right on the spot from the touch screen.

Room Scheduling Touch Screens end the wasteful practice of searching the corridors for an available room. They eliminate confusion over which room is booked — by whom, and for how long — and allow attendees to verify they're in the right place before entering a room. They help organizations to maximize productivity and get the most usable time out of every room.

Crestron Room Scheduling Touch Screens are designed to be installed as part of a complete enterprise room scheduling solution using [Fusion RV®](#) Remote Asset Management Software.

Form and Function

The TSS-752 Room Scheduling Touch Screen features a brilliant 7 inch (178 mm) widescreen display with lots of space for displaying essential meeting and scheduling information all at once without having to flip through multiple pages. Crestron Smart Graphics™ delivers a dynamic, gesture-driven user experience with many customizable features. Capacitive touch screen technology affords nimble touch response for navigating the intuitive on-screen interface. Soft-touch buttons to the right of the touch screen offer an alternate method for navigating the on-screen



interface. Side-mounted, multi-color LED beacons provide clear indication of a room's status down long corridors.

With its clean, modern appearance, the TSS-752 makes an elegant statement in any environment including office buildings, conference centers, hotels, and universities. A choice of mounting options allows the TSS-752 to be installed in places other touch screens just can't go. It can be installed on a wall over a standard 2-gang electrical box, or mounted to virtually any flat surface — even glass, granite, or marble.^[1]

Enhanced Room Scheduling

The TSS-752 is optimized for use with Crestron Fusion RV software, enabling tight integration with popular scheduling applications like Microsoft® Exchange, Office 365®, IBM® Notes®, CollegeNET® R25®, and Google Calendar™. Through its color touch screen, the TSS-752 provides advanced room scheduling capabilities that can be customized to suit the needs of any organization.



- **Schedule View** – Displays a clear, at-a-glance view of the current reservation along with upcoming reservations and available time slots on a scrolling calendar ribbon. New reservations can be scheduled on the spot.
- **Find** – Allows you to quickly search all the rooms on the network, and reserve any room nearby, without leaving the touch screen you're at.
- **End Now** – Allows you to end a reservation early, making the room available to others immediately.
- **Extend** – Allows you to extend the current reservation if a meeting is running over and the room is still available.
- **Details** – Provides additional information about a reservation.
- **Check In** – This option requires the meeting organizer to check in before a meeting to confirm the reservation. If no one checks in, the

TSS-752 7" Room Scheduling Touch Screen

room can automatically become available to others.

- **Availability Threshold** – Reserves extra setup time ahead of the actual scheduled event. Eliminates the need to schedule a separate reservation for setup of furniture, refreshments, staging, and AV before a meeting, luncheon, or other event.
- **Custom Backgrounds** – Allows you to change the background images that appear on each touch screen. Company logos and other custom graphics can be uploaded to the Fusion RV server, or any Web server, enabling the graphics to be changed at any time by simply uploading a new image file to the server.
- **Localization** – Supports international fonts and formats in combination with Fusion RV software.
- **Broadcast Messaging** – Allows display of text bulletins, announcements, and other messages on the touch screen. Emergency broadcasts can be accompanied by an alert sound, while non-emergency messages display on the screen without disrupting its normal use.
- **PIN Code Authorization** – Allows use of a 4-digit PIN code to restrict access to certain functions such as reserving a room through the touch screen, viewing a private reservation, viewing details, checking into a meeting, extending a reservation, ending a reservation early, or accessing the touch screen configuration page.

Occupancy Sensing

Fusion RV supports the use of room occupancy sensors to detect when no one has shown up for a scheduled meeting. In such an event, the current reservation can be cancelled automatically to make the room available to others. Occupancy sensors do not connect directly to the TSS-752. They communicate with Fusion RV via connection to a [Crestron control system](#). Crestron [GLS Series Occupancy Sensors](#)^[2] are available in a variety of types to support connection to the control system using Cresnet®, infiNET EX®, or a Versiport I/O port.

Custom User Mode

Just like any other Crestron touch screen, the TSS-752 can be custom programmed for all types of applications. The TSS-752 uses Smart Graphics to deliver the ultimate user experience for controlling AV, lighting, shades, HVAC, and other functions. Additional enhancements include support for H.264 streaming video, Rava™ SIP intercom, and audio feedback.



TSS-752-B-S - Side View with optional Multi-Surface Mounting Kit (sold separately)



TSS-752-B-S - Shown in "Reserved" state

Single-Wire Connectivity

A simple Ethernet LAN connection is all that is required to wire the TSS-752, containing all control, video, intercom, and power signals within a single wire.

Power over Ethernet

Using PoE technology, the TSS-752 gets its operating power right through the LAN wiring. PoE (Power over Ethernet) eliminates the need for a local power supply or any dedicated power wiring. A PoE Injector ([PWE-4803RU](#)^[2]) simply connects in line with the LAN cable at a convenient location. Crestron PoE switches ([CEN-SW-POE-5](#), [CEN-SWPOE-16](#), or [CEN-SWPOE-24](#)^[2]) may also be used to provide a total networking solution with built-in PoE.

Simple, Versatile Mounting

The TSS-752 installs easily on virtually any mounting surface. Using the mounting plate provided, it can be attached directly to a US, UK, or European electrical box (see specifications). For impenetrable surfaces, such as decorative glass, granite, marble, plaster, smooth stone and masonry, Crestron offers the Multi-Surface Mount Kit ([TSS-752-MSMK](#)^[2]), which comes complete with a low-profile rear shell, adhesive mounting plate, and wire raceway.

SPECIFICATIONS

Touch Screen Display

Display Type: TFT Active matrix color LCD
Size: 7 inch (178 mm) diagonal
Aspect Ratio: 15:9 WVGA
Resolution: 800 x 480 pixels
Brightness: 300 nits (cd/m²)
Contrast: 350:1
Color Depth: 18-bit, 262k colors
Illumination: Edgelit LED
Viewing Angle: ±70° horizontal, ±65° vertical
Touch Screen: Projected Capacitive

TSS-752 7" Room Scheduling Touch Screen

Buttons

Hard Keys: (5) Projected capacitive pushbuttons for menu navigation
Reset: (1) Miniature pushbutton on rear panel for hardware reset

Room Status Indicators

(2) Side-mounted tri-color red/green/blue LED beacons for room status indication

Memory

LPDDR2 RAM: 1 GB
Flash: 4 GB
Maximum Project Size: 512 MB

Graphics Engine

Supports Smart Graphics™ [3]

Crestron Fusion® Language Support

Chinese (Simplified), Chinese (Traditional), Dutch (Netherlands), English (US), English (UK), French, German, Italian, Japanese, Russian, Spanish

Communications

Ethernet: 10/100 Mbps, auto-switching, auto-negotiating, auto-discovery, full/half duplex, DHCP, IEEE 802.3af and 802.3at Type 1 compliant

Video^[4]

Streaming Formats: H.264 (MPEG-4 part 10 AVC), MJPEG

Audio^[4]

Features: Built-in microphone and speakers, Rava™ SIP Intercom
Audio Feedback Formats: MP3

Connections

LAN PoE: (1) 8-wire RJ45 with 2 LED indicators;
10Base-T/100Base-TX Ethernet port, Power over Ethernet compliant;
Green and yellow LEDs indicate Ethernet port status

Power Requirements

Power over Ethernet: IEEE 802.3at Type 1 (802.3af compatible) Class 3 (12.95W) PoE Powered Device

Environmental

Temperature: 32° to 112°F (0° to 45°C)
Humidity: 10% to 90% RH (non-condensing)
Heat Dissipation: 28 BTU/hr

Enclosure

Construction: Plastic, smooth black or white finish
Mounting: Surface mount over a 2-gang electrical box or plaster ring,

horizontally-oriented 1-gang electrical box or plaster ring, 2-gang European (DIN 49073) electrical box, 2-gang UK (BS 4662) electrical box, or small cutout; optional multi-surface mounting kit sold separately

Dimensions

Height: 4.75 in (121 mm)
Width: 7.61 in (194 mm)
Depth: 1.47 in (38 mm)

Weight

17.0 oz (481 g)

MODELS & ACCESSORIES

Available Models

TSS-752-B-S: 7" Room Scheduling Touch Screen, Black Smooth
TSS-752-W-S: 7" Room Scheduling Touch Screen, White Smooth

Available Accessories

TSS-752-MSMK: Multi-Surface Mount Kit
PWE-4803RU: PoE Injector
CEN-SW-POE-5: 5-Port PoE Switch
CEN-SWPOE-16: 16-Port Managed PoE Switch
CEN-NVS200: Network Video Streamer
SW-VMK-WIN: TouchPoint® Virtual Mouse & Keyboard Software for Windows®

Notes:

1. Multi-surface mounting kit sold separately.
2. Item(s) sold separately.
3. Supports Smart Graphics only. Not compatible with traditional UI projects.
4. Enabled through custom programming. Not used for typical room scheduling applications.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Crestron, the Crestron logo, Cresnet, Crestron Fusion, Fusion RV, infinET EX, Rava, Smart Graphics, and TouchPoint are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. CollegeNET and R25 are either trademarks or registered trademarks of CollegeNET, Inc. in the United States and/or other countries. Google Calendar is either a trademark or registered trademark of Google Inc. in the United States and/or other countries. IBM and Notes are either trademarks or registered trademarks of International Business Machines Corporation in the United States and/or other countries. Microsoft, Office 365, Windows is either a trademark or registered trademark of Microsoft Corporation in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2014 Crestron Electronics, Inc.

TSS-752 7" Room Scheduling Touch Screen

