# Comark Pressure Meters

Comark pressure meters combine high accuracy with speed of response and offer the option of ATEX certified Intrinsically Safe models.

The C9500 instruments have twin inputs for gauge or differential pressures and positive or negative (vacuum) pressure measurement.

Typical applications include boiler flue draft, air conditioning filters, laboratories and clean rooms, process pressures, service and maintenance and the calibration of other instruments.

- **ATEX compliant** certified to  $\langle \mathcal{E}_x \rangle$  II 1 G EEx ia IIC T4 Ga Baseefa03ATEX0079
- Selectable pressure units\* PSI, mbar, Bar, inH2O, inHg, mmHg, Torr, Pa, KPa, mmH<sub>2</sub>O, cmH<sub>2</sub>O, Kgcm<sup>-2</sup>
- Positive or negative (vacuum) pressure measurement
- Adjustable zero value
- Maximum, minimum pressure and hold function
- Averaged reading function
- Over-range indication
- Selectable auto switch off
- Silicone protection option available for liquid pressure measurement

Supplied with tubing and connectors, plus hard carry case for IS Models

\* Dependant on model



Comark is the leading manufacturer and supplier of a wide range of electronic measurement instruments for temperature, humidity and pressure



## **Technical Specification**

Standard		C9551	C9553	C9555	C9557
Intrinsically Safe		C9501/IS	C9503/IS	C9555/IS	C9507/IS
PSI	Range	0 to ±2.031	0 to ±5.076	0 to ±30.46	0 to ±101.05
	Resolution	0.001	0.001	0.001	0.01
mBar	Range	0 to ±140	0 to ±350	0 to ±2100	0 to ±7000
	Resolution	0.1	0.1	0.1	1
Bar	Range Resolution	-	-	0 to ±2.100 0.001	0 to ±7.000 0.001
inH <sup>2</sup> O	Range	0 to ±56.2	0 to ±140.5	0 to ±843.1	0 to ±2810
	Resolution	0.01	0.01	0.1	0.1
inHg	Range	0 to ±4.134	0 to ±10.34	0 to ±62.01	0 to ±206.7
	Resolution	0.001	0.001	0.01	0.01
mmHg	Range	0 to ±105.0	0 to ±262.5	0 to ±1575	0 to ±5250
	Resolution	0.01	0.01	0.1	1
Torr	Range	0 to ±105.0	0 to ±262.5	0 to ±1575	0 to ±5250
	Resolution	0.01	0.01	0.1	1
Pa	Range Resolution	0 to ±14000 1	-	-	-
KPa	Range	0 to 14.00	0 to ±35.00	0 to ±210.0	0 to ±700.0
	Resolution	0.001	0.01	0.01	0.1
mmH <sup>2</sup> O	Range Resolution	0 to ±1428 0.1	0 to ±3569 1	-	-
cmH <sup>2</sup> O	Range Resolution	0 to ±142.8 0.01	-	0 to ±2141 0.1	0 to ±7138 1
Kgcm- <sup>2</sup>	Range	0 to ±143	0 to ±0.357	0 to ±2.141	0 to ±7.138
	Resolution	0.001	0.001	0.001	0.001

### **WARRANTY**

All Comark instruments have a minimum one year warranty unless otherwise stated. The warranty period for temperature probes is for six months and all other probes and electrodes are unwarranted because the conditions of use are beyond our control. The Comark warranty covers manufacturing defects and component failures on all products returned to Comark premises and applies worldwide. The warranty does not affect your statutory rights. In line with our policy of continuous development we reserve the right to alter any product specifications without notice. All products are covered by our Quality Management System which is compliant with BS EN ISO 9001:2008 for the design, manufacture, supply, service, repair and recalibration of electronic measuring instruments and equipment.

Maximum Over/	6 PSI/ 1	5PSI/	90PSI/	200PSI/		
Under Pressure	400mbar 1	1000mbar	6200mbar	13700mbar		
Accuracy at +23°C	±0.2% of full scale					
Repeatability at +23°C	±0.1% of full scale					
Mean Temperature						
Coefficient of Reading	Better than 0.1% per °C					
Operating Range						
Temperature	0°C to +40°C					
Humidity	10 to 90% RH non condensing					
Environmental Rating	IP67, BS EN60529, IEC 529					
Protection Levels (IS Models only)	⟨⟨⟨⟨⟨Ex⟩⟩ II 1G EEx ia IIC T4 Ga Baseefa03ATEX0079					
	(Certification applicable at atmospheric pressure)					
Connections	1/8" BSP Female					
Battery Type	6F22 MN 1604, PP3 VT3 UCAR 9V					
Battery Life	90 Hours					

Distributed by:

#### **Comark Instruments**

52 Hurricane Way Norwich, Norfolk NR6 6JB, United Kingdom

Tel: 0844 815 6599 0844 815 6598

Email: sales@comarkinstruments.com



#### **Comark Instruments (USA)**

PO Box 500 Beaverton, OR 97077, USA

Tel: (800) 555 6658 Fax: (503) 644 5859 Email: sales@comarkusa.com

