



Optics

- Lamp options:
 - 1 or 2 x 26W TC-T
 - 1 or 2 x 32W TC-T
 - 1 or 2 x 42W TC-T
- Pure aluminium anodised low glare diamond facet optic

Body

- Spun aluminium body finished in white
- Three point fixing
- 20mm cable way
- Integrated low energy LED emergency (available with the long version only)

Order Codes

Short

TC-T 1 x 26/32/42W	Multi Watt Ballast	SXSH126-42
TC-T 2 x 26/32/42W	Multi Watt Ballast	SXSH226-42

Long

TC-T 1 x 26/32/42W	Multi Watt Ballast	SXLH126-42
TC-T 2 x 26/32/42W	Multi Watt Ballast	SXLH226-42

DALI Dimming (Long Version Only)

TC-T 1 x 26W	SXLY126
TC-T 1 x 32W	SXLY132
TC-T 1 x 42W	SXLY142
TC-T 2 x 26W	SXLY226
TC-T 2 x 32W	SXLY232
TC-T 2 x 42W	SXLY242

Options

EMERGENCY*	Add suffix /EM	i.e. SXLD126/ EM
EASYTEST*	Add suffix /ET	i.e. SXLD126/ ET
COMEPS*	Add suffix /EP	i.e. SXLD126/ EP

*Note: Emergency and dimming are not available in the short version



Low Energy Emergency LED




Short Body

Lamp Performance


Wattage	IL@25°C	Lamp Life
1 x 26W TC-T	1800	13,000hrs
1 x 32W TC-T	2400	13,000hrs
1 x 42W TC-T	3200	13,000hrs

Dimensions



Version	Ø	H	KG	KG
Short	255	205	1.3	–
Long	255	275	2.1	2.6

Photometric Performance




2 x 26W TC-T
Diamond Facet
Reflector
• LOR = 67%
• SHR MAX = 1.52

Utilisation Factors UF(F)

Room Reflectance	Room Index
C W F	1.00 3.00 5.00
0.70 0.50 0.20	0.47 0.61 0.65

Performance Guide

Lamps	Illuminance	Spacing
2 x 26W TC-T	185 lux	3.0m x 3.0m



Maintenance:
0.8
Reflectance:
70/50/20
Ceiling Height:
2.7m
Working Plane:
0.0m

To Specify

Surface mounted downlight with spun aluminium body and pure aluminium diamond facet reflector – as Whitecroft Lighting MIRAGE SX