



Starline

- Up to IP65 when used in conjunction with additional waterproof connector
- Aluminium slimline channel complete with fixing brackets
- Complete with 150mm connecting cables, with standard connectors, at each end for ease of installation
- Non IP65 plug & play connectors for simple connection pre-wired
- Beam angle - 110°
- High brightness LEDs in linear array mounted in aluminium alloy channel and covered by silicone resin

Driver

- 24V DC electronically stabilised constant voltage driver

Note: Drivers are not IP rated and should not be used in non weatherproof locations



Order Codes

Concert Starline

| | | |
|--------------------------|---------|------------|
| Starline 600 Warm White | 10 Watt | CNSL3K600 |
| Starline 600 Cool White | 10 Watt | CNSL4K600 |
| Starline 1200 Warm White | 20 Watt | CNSL3K1200 |
| Starline 1200 Cool White | 20 Watt | CNSL4K1200 |


Driver

| | | |
|---------|------------------------------|---------|
| 20 Watt | Runs upto 2 x 10W or 1 x 20W | CNSLD20 |
| 75 Watt | Runs upto 7 x 10W or 3 x 20W | CNSLD75 |

Accessories

| | |
|---|-------|
| QUICK WATERPROOF CONNECTOR (FOR LINKING STRIPS) | CNUY2 |
|---|-------|

Dimensions



| Version | L | W | H | KG |
|---------------|------|----|-----|-----|
| Starline 600 | 620 | 20 | 6.2 | 0.1 |
| Starline 1200 | 1220 | 20 | 6.2 | 0.2 |

To Specify

Linear LED strip luminaire with extruded aluminium body. Complete with pre-wired cables and connectors. IP65 when used with quick fix waterproof connectors – as Whitecroft Lighting CONCERT STARLINE