

kololo IP65 F

IP65 surface mounted
amenity luminaire



Optics

- Light Output Options:
 - 1 x 18/26W TCD
 - 1 x 28/38W 2D T5
- Polycarbonate opal diffuser

Body

- Surface mounted as standard
- 300mm or 400mm diameter in cast aluminium with injection moulded base
- IP65
- Finished in silver or black
- Optional integral 3 hour emergency
- Plastic twist clip lock mechanism
- Optional trim ring or grill front attachment for alternative aesthetic

Order Codes

300mm IP65	HF Gear	3 hr Emergency
1 x 18W TCD	KF6H3118S	KF6H3118SEM
1 x 26W TCD	KF6H3126S	KF6H3126SEM

400mm IP65	HF Gear	3 hr Emergency
1 x 28W 2D T5	KF6H4128S	KF6H4128SEM
1 x 38W 2D T5	KF6H4138S	KF6H4138SEM

Attachments	300mm	400mm
Trim ring silver	K6ATR3S	K6ATR4S
Grill silver	K6AGR3S	K6AGR4S

Options		
BLACK	Replace S with B	i.e. KF6H3118B



With grill attachment




Without attachments




With Trim Ring

Dimensions



Version	Ø	H	KG	KG
300mm surface	300	95	2.1	2.5
400mm surface	400	95	3.5	3.9

Photometric Performance



400mm
1 x 38W 2D T5
• LOR = 49.4
• SHR MAX = 49.4

Lamp Performance

Wattage	IL@25°C	Lamp Life
1 x 28W 2D T5	2150	21,000hrs
1 x 38W 2D T5	3020	21,000hrs

Utilisation Factors UF(F)

Room Reflectance	Room Index
C W F	1.00 3.00 5.00
0.70 0.50 0.20	0.33 0.47 0.51

To Specify

Surface mounted circular IP65 bulkhead luminaire in 300 or 400mm diameter. Polycarbonate opal diffuser. Trim ring and grill front attachments available. Optional integral 3 hour emergency - as Whitecroft Lighting KOLO IP65 F