

iTrack line attachments

T5 fluorescent
batten attachments



Attachments

- Cross blade louvre with push and lock fitting for efficient installation
- Aluminium seam to join reflectors linked in a continuous line
- Toughened plastic end cap to fit all reflector sizes and prevent light bleed
- Order reflectors and louvres separately (louvres must be used in conjunction with appropriate reflectors)

Order Codes

Lamella louvres

Medium louvre 28/54W	LLM4
Medium louvre 35/49/80W	LLM5
Wide louvre 28/54W	LLW4
Wide louvre 35/49/80W	LLW5
Asymmetric louvre 28/54W	LLA4
Asymmetric louvre 35/49/80W	LLA5

Continuous row reflector seams

Narrow reflector seam - pair	LCRSN
Medium reflector seam - pair	LCRSM
Wide reflector seam - pair	LCRSW
Asymmetric reflector seam - pair	LCRSA

Reflector end caps

Narrow reflector cap - pair	LRN/EC
Medium reflector cap - pair	LRM/EC
Wide reflector cap - pair	LRW/EC
Asymmetric reflector cap - pair	LRA/EC

Options

CONTINUOUS LOUVRE	Insert C	i.e. LLCM4
-------------------	----------	------------



End Cap



Continuous Row Reflector Seam



Cross Blade Louvre