

iTrack line reflectors

**T5 fluorescent
batten reflectors**



Reflectors

- 5 aluminium reflector options available
 - extra narrow
 - narrow
 - medium
 - wide
 - asymmetric
- MIRO 5 zero iridescent semi-specular reflector
- Symmetric reflectors provide downward light over narrow, medium or wide areas
- Asymmetric reflector provides directional lighting on vertical surfaces
- All reflectors fit single or twin lamp batters

Order Codes

Extra narrow reflector*

1 or 2 x 28/54W
1 or 2 x 35/49/80W

LREN4

LREN5

Narrow reflector

1 or 2 x 28/54W
1 or 2 x 35/49/80W

LRN4

LRN5

Medium reflector

1 or 2 x 28/54W
1 or 2 x 35/49/80W

LRM4

LRM5

Wide reflector

1 or 2 x 28/54W
1 or 2 x 35/49/80W

LRW4

LRW5

Asymmetric reflector

1 or 2 x 28/54W
1 or 2 x 35/49/80W

LRA4

LRA5

*Note the extra narrow reflector is not available with any of the iTrack Line attachments



Narrow



Medium



Wide






Asymmetric

Dimensions

Extra Narrow



Narrow

Medium




Wide


Asymmetric




Photometric Performance




1 x 35W T5
narrow reflector
• LOR = 91.5%



1 x 35W T5
medium reflector
• LOR = 93.3%



1 x 35W T5
wide reflector
• LOR = 94.1%



1 x 35W T5
asymmetric reflector
• LOR = 92.3%