

Optics

- Power consumption
 - 10W maintained
 - 7W non-maintained
- Clear polycarbonate TP(a) lens with linear prisms
- Wide light distribution
- 16 long life white LEDs
- Low tack self adhesive legends to be ordered separately
 - 30 metre viewing distance
- Normal lamp output 90 lumen
- Emergency lamp output 90 lumen
- Legends supplied in accordance with BS 5266-1 2011 (ISO7010)

Body

- High impact polycarbonate tp(a) body finished light grey
- Surface and semi recessed
 - (with semi-recessing bezel kit – to be ordered separately)
- IP54
- 3 hour maintained (may be wired as non-maintained)
- High temperature Ni-Cd battery with constant current charger and LED charge indicator
- Hinged gear tray for easy maintenance
- Cable entry options along the sides and back of the body

Order Codes

| Concert Tereo | | 3 hr Emergency |
|------------------------|-------------------|----------------|
| LED Emergency Bulkhead | 3 hour maintained | TERNM3 |

Options


| | | |
|--------------------|----------------|----------------|
| LEFT LEGEND | | TER/AL/7010 |
| RIGHT LEGEND | | TER/AR/7010 |
| DOWN LEGEND | | TER/AD/7010 |
| UP LEGEND | | TER/AU/7010 |
| SEMI RECESSING KIT | | TER/SRK |
| EASYTEST | Add suffix /ET | i.e. TERNM3/ET |
| COMEPS | Add suffix /EP | i.e. TERNM3/EP |

Note: Legends to be ordered separately



Semi-Recessing Bezel Kit

Dimensions



Legends



Up



Down



Left



Right

To Specify

Surface / Semi recessed LED bulkhead complete with all polycarbonate tp(a) construction. 3 hour self contained non maintained / maintained. – as Whitecroft Lighting Tereo