

egress recessed

recessed emergency
luminaire



Optics

- Lamp options:
 - 1 x 8W T5
- Normal lamp output 400 lumens
- Emergency lamp output 100 lumens

Body

- Fully recessed high grade polycarbonate body mounted in ceiling tile with winged fixings adjustable from below with white lip trim, recess depth 70mm
- 3 hour maintained, non-maintained or mains voltage versions
- High temperature Ni-Cd battery with constant current charger and LED charge indicator
- Cable entry locations at rear
- Ambient 0 – 25°C
- Circuit Watts 8W (non-maintained), 20W (maintained) and 12W (mains)



Order Codes


| Egress Recessed | | 3 hr Emergency |
|-----------------|-----------------------|----------------|
| T5 1 x 8W | 3 hour non-maintained | EGRXNMF8 |
| T5 1 x 8W | 3 hour maintained | EGRXMF8 |
| T5 1 x 8W | mains voltage | EGRXF8 |

Options

| | | |
|----------|----------------|------------------|
| EASYTEST | Add suffix /ET | i.e. EGRXNMF8/ET |
| COMEPS | Add suffix /EP | i.e. EGRXNMF8/EP |

Note: Available with COMET. Please refer to our sales office for details

Dimensions



| L | W | H | KG |
|-----|-----|----|-----|
| 420 | 172 | 83 | 1.5 |

To Specify

Fully recessed 8W T5 IP20 emergency luminaire in 3 hour self contained maintained, non-maintained or mains voltage versions. Polycarbonate body recess <70mm mounted in ceiling tile with winged fixings. High temperature Ni-Cd battery with constant current charger and LED charge indicator – as Whitecroft Lighting EGRESS RECESSED