









## **Optics**

- Max 30m viewing distance
- Lamp options:
  - 1 x 8W T5
- Screen printed legend panel retained by screw fixed front frame to be ordered separately
- Legends supplied in accordance with BS 5266-1 2011 (ISO7010)

### **Body**

- Rigid white powder coated steel housing and gear and lamp tray. Substantial downlight panels in body designed to give illumination at floor level
- 3 hour maintained or non-maintained versions
- High temperature Ni-Cd battery with constant current charger and LED charge indicator
- Cable entry via knockouts in sides and rear
- Ambient 0° 25°C
- Circuit Watts 8W (20W maintained version)



## **Order Codes**

Exit		3 hr Emergency
T5 1 x 8W	3 hour non-maintained	SENEXNMF8
T5 1 x 8W	3 hour maintained	SENEXMF8


#### Options

EASYTEST	Add suffix /ET	i.e. SENEXNMF8/ <b>ET</b>
COMEPS	Add suffix /EP	i.e. SENEXNMF8/ <b>EP</b>
LEFT LEGEND		SENLPL/7010
RIGHT LEGEND		SENLPR/7010
DOWN LEGEND		SENLPD/7010
UP LEGEND		SENLPU/7010

Note: Legends to be ordered separately

Available with COMET. Please refer to our sales office for details

#### **Dimensions**



# Legends





)





To Specify

8W T5 IP20, 3 hour self contained maintained or non-maintained emergency exit sign with rigid white powder coated steel body and gear and lamp tray. Screen printed legend panels retained by screw fixed front frame. High temperature Ni-Cd battery with constant current charger and LED charge indicator – as Whitecroft Lighting EXIT