pathfinder LED recessed exit sign



Optics

- 22m viewing distance
- 3 x 1W LEDs
- LEFT, RIGHT, UP and DOWN acrylic legend panel to be ordered separately

Body

- Brushed steel body finished silver
- Housing has adjustable arms to simplify installation
- Smaller than conventional recessed exit signs making installation more attractive
- Supplied complete with driver
- Input voltage 24V DC
- Current consumption: 0.15A

Note: LED recessed exit sign can only be used as part of a Pathfinder system



Order codes

LED Recessed Exit Sign


3 x 1W LED Silver Ceiling Mounted **PFDRECESSED**

Legends

0		
DOWN LEGEND	SINGLE SIDED	PFDRESSD
UP LEGEND	SINGLE SIDED	PFDRESSU
LEFT LEGEND	SINGLE SIDED	PFDRESSL
RIGHT LEGEND	SINGLE SIDED	PFDRESSR
DOWN LEGEND	DOUBLE SIDED	PFDREDSD
UP LEGEND	DOUBLE SIDED	PFDREDSU
TO SIDE LEGEND	DOUBLE SIDED	PEDREDST

Note: Legends to be ordered separately

Dimensions



Legends









To Specify

Central battery, central test LED emergency lighting system. Fully addressable LED emergency lighting points. Control unit with programmable interface – as Whitecroft Lighting PATHFINDER