



Optics

- Max 27m viewing distance
- Lamp options:
 - 1 x 8W T5
- 8mm thick Perspex legend panels, double sided, to be ordered separately
- Maximum projection below the ceiling 175mm
- Legends supplied in accordance with BS 5266-1 2011 (ISO7010)

Body

- Fully recessed white high grade polycarbonate body mounted in ceiling tile with winged fixings adjustable from below with white lip trim, recess depth 83mm. Light dispersal cover with slot for legend panel
- 3 hour maintained or non-maintained versions
- High temperature Ni - Cd battery with constant current charger and LED charge indicator
- Ambient 0 – 25°C
- Input voltage 230/240V – 50Hz
- Circuit Watts 8W (20W maintained version)



Order Codes


Slot		3 hr Emergency
T5 1 x 8W	3 hour non-maintained	SLOTNMF8
T5 1 x 8W	3 hour maintained	SLOTMF8

Options


EASYTEST	Add suffix /ET	i.e. SLOTNMF8/ET
COMEPS	Add suffix /EP	i.e. SLOTNMF8/EP
LEFT/RIGHT LEGEND	(double sided)	SLOTLPL/RD/7010
DOWN LEGEND	(double sided)	SLOTLPDD/7010
UP LEGEND	(double sided)	SLOTLPUD/7010

Note: Available with COMET. Please refer to our sales office for details

Dimensions



Legends



To Specify

Recessed 8W T5 IP20 blade exit sign in 3 hour self contained maintained or non-maintained versions. Light dispersal cover with slot for 8mm thick Perspex legend panels, projection below the ceiling <176mm, polycarbonate body recess <83mm mounted in ceiling tile with winged fixings. High temperature Ni-Cd battery with constant current charger and LED charge indicator – as Whitecroft Lighting SLOT