

IP40 dedicated consulting room luminaire












Optics

- Lamp options:
 - -3 x 24W T5
- Micro prism side controllers or living louvres covered by clear polycarbonate
- Satine Blend central diffuser for lamp diffusion
- Framed polycarbonate sheet for ease of cleaning
- Picture options for central diffuser to add feature

Body

- Sheet steel body and frame with a choice of comfort and brightness controlled optics. Combines Duo office lighting excellence with infection control and clean area expertise
- IP40 rated



Micro Prism Diffuser with Opal Central Diffuser



Living Louvre with Sky Image

duo® consult

Order Codes

| Micro Prism Optic | HF Gear | 3 hr Emergency |
|-------------------|----------|----------------|
| T5 3 x 24W | DCNMH324 | DCNMH324EM |
| | | |

Living Louvre Optic 3 hr Emergency HF Gear DCNVH324 DCNVH324EM T5 3 x 24W

Options

i.e. DCNMY324 DALI DIMMING Replace H with Y SWITCH DIMMING Replace H with X i.e. DCNMX324 Add suffix /ET i.e. DCNMH324/ET COMET Add suffix /CT i.e. DCNMH324/CT Add suffix /EP i.e. DCNMH324/EP

Image Options


Add suffix /PA to order code i.e. DCNMH324/PA Alternative images: Replace PA with PB, FA, FB, FC or FD depending on


Note: Inclusion of an image can reduce light output by up to 25%

Printed Images









Photometric Performance



Utilisation Factors UF(F) Room Reflectance Room Index

Living Louvre
• LOR = 59.3% • SHR MAX = 1.85

Lamp Performance

IL@25°C Lamp Life 1 x 24W T5





Ceiling Integration

compatibility matrix -See page 404

Exposed T Grids

T15/T25 Pull up


Spring T Grids

Armstrong - Orcal 1800/3000 Burgess - Clip in/Abar

Plasterboard

Prepared aperture

Dimensions



598 598 100 536 536 5.9 6.9

To Specify

Consulting room T5 luminaire with IP40 easy clean front diffuser and living louvre, micro prism controller or picture options to add feature – as Whitecroft Lighting DUO CONSULT