

mirage MX24 anti-ligature

anti-ligature recessed
downlighter



Optics

- Lamp options:
 - 2 x 18W TC-D
 - 2 x 26W TC-D
- Plain silver reflector with high impact 5mm thick polycarbonate cover

Body

- Die cast body and inner bezel
- Body screw fixed to ceiling before front bezel is located
- Front bezel secured by retained tamper proof screws
- Can be used with technical louvre and dimming control gear for night lighting applications
- IP44 from room side



Technical Louvre

Order Codes


Mirage MX24 Anti-Ligature	HF Gear	3 hr Emergency
TC-D 2 x 18W	MX24ALH218P	MX24ALH218PEM
TC-D 2 x 26W	MX24ALH226P	MX24ALH226PEM

Options

DALI DIMMING	Replace H with Y	i.e. MX24ALY218P
SWITCH DIMMING	Replace H with X	i.e. MX24ALX218P
EASYTEST	Add suffix /ET	i.e. MX24ALH218P/ET
COMET	Add suffix /CT	i.e. MX24ALH218P/CT
COMEPS	Add suffix /EP	i.e. MX24ALH218P/EP
SPECIAL TOOL REQUIRED FOR ACCESS AND FIXING		HAL-KEY
TECH LOUVRE	Add suffix T	i.e. MX24ALH218PT
	For emergency	i.e. MX24ALH218PTM


Performance Guide

Lamps	Illuminance	Spacing
2 x 26W TC-D	220 lux	2.4m x 2.4m




Maintenance: 0.8
Reflectance: 70/50/20
Ceiling Height: 2.7m
Working Plane: 0.8m

Dimensions



Photometric Performance



2 x 26W TC-D
• LOR = 38.8%
• SHR MAX = 1.61

Lamp Performance

Wattage	IL@25°C	Lamp Life
1 x 18W TC-D	1200	13,000hrs
1 x 26W TC-D	1800	13,000hrs

Utilisation Factors UF(F)

Room Reflectance	Room Index
C W F	1.00 3.00 5.00
0.70 0.50 0.20	0.32 0.40 0.42

To Specify

Pressed steel and extruded aluminium bodied TC-D compact fluorescent anti-ligature down-lighter with high frequency gear integral to body and plain silver reflector with optional technical louvre. High impact 5mm thick polycarbonate cover retained by mounting ring and spun bezel in 0.9mm zinc steel finished white and secured by 3 – M5 x 20 tamper proof screws – as Whitecroft Lighting MIRAGE MX24 AL