

- Uses passive infra red detection technology
- For recessed or surface mounting 360° detector
- Off delay of 20 minutes from last observed movement
- 10 second walk test mode
- Switches up to 6A of lighting
- Maximum range of 6m Ø (based on 2.5m mounting height)
- Maximum recommended mounting height 3m
- Photocell measures daylight penetration and holds off luminaires if adequate daylight is present (COMRA only)
- Remote switching via hand held controller (COMHHC)
- Recessed version supplied complete with 3m lead
- 'THETA' hub detector supplied with 3m lead and 7 way plug for connection to CPDMTHETA (see page 303)



Order Codes

PIR Detector with Photocell

Recessed

Recessed THETA

COMRA
COMRATHETA

PIR Detector without Photocell

Recessed

Surface Mounting

COMRAU
COMRAUSM

Options

Plasterboard Fixing Kit

COMPB

Optional Command Fast Link Connector

CFL 4 POLE

Add suffix /CFL4P

i.e. COMRA/CFL4P


CFL 6 POLE

Add suffix /CFL6P


i.e. COMRA/CFL6P

Dimensions

Recessed



Surface




Version	Ø	H	CAØ
Recessed	65	115	50*
Recessed THETA	65	115	64

Ø	H
100	72

* When using CFL 6 Pole CAØ on recessed version is 64

Detection Range



Accessories (See Page 309)



Handheld Programmer COMPTC for COMRA Photocell Programming only



Handheld Controller COMHHC