

# cygnus SX

## LED post top lantern for outdoor applications



### Optics

- Light output options:
  - 4004 lumens (4000K - 53W)
- Symmetrical distribution
- Zero light pollution
- UV stabilised polycarbonate clear diffuser
- 70% light output after 60,000 hours life

### Body

- Die cast aluminium
- Coated for corrosion and saline environment resistance
- IP66 IK08 rated protection
- 60mm diameter post top spigot
- Finished in Graphite Grey or Silver
- Supplied with IP67 rated 3 pole plug and socket
- Suitable for ambient temperatures between -20°C to +40°C




### Order Codes

Cygnus SX  
4004 lumen (53W)      Graphite Grey      **CYX14KG**

Options  
SILVER      Replace G with **S**      i.e. CYX14KS

### Dimensions




Ø      H      KG  
375      765      7.7

WINDAGE M<sup>2</sup>: 0.165

### LED Performance

Colour Temp	Ra (CRI)	Life Expectancy	Colour Consistency
4000K	≥ 80	L <sub>70</sub> (60,000hrs)	MacAdam 4 SDCM

### Photometric Performance



53W 4004 lumen  
• LOR = 100%

### To Specify

IP66 LED post top lantern with tapered die cast aluminium body. With symmetrical distribution having zero upward light – as Whitecroft Lighting CYGNUS SX.