

sirocco disc

Slimline circular LED post top lantern for outdoor applications

LED IP65 60+

Optics

- Light output options:
 - 5200 lumens (4000K - 83W)
- Wide symmetrical distribution
- Zero light pollution
- 70% light output after 60,000 hours life

Body

- Die cast aluminium with integrated fins for heat dissipation
- Coated for corrosion and saline environment resistance
- IP65 IK08 rated protection
- Post top mounting with spigot to suit dedicated bracket
- Finished in Silver or Graphite Grey
- Supplied with IP67 rated 3 pole plug and socket
- Automatic temperature regulation
- Voltage surge protection
- Simple top cover access
- Suitable for ambient temperatures between -20°C to +40°C
- 5m maximum recommended mounting height
- Requires dedicated bracket (order separately)



Order Codes

Sirocco Disc
5200 lumens (83W) Colour: Silver **SDL14KS**


Accessories

Single curved bracket Silver **SDBKT1S**
Twin curved bracket Silver **SDBKT2S**

Options


GRAPHITE GREY Replace S with G i.e. **SDL14KG**

Dimensions



Ø H D Ø_EXT KG
730 248 50 60 8.5

Windage M²: 0.04




Version	H	W	Ø_INT
BKT1	1000	356	60
BKT2	1000	635	60

LED Performance

Colour Temp	Ra (CRI)	Life Expectancy	Colour Consistency
4000K	≥ 70	L ₇₀ (60,000hrs)	MacAdam 4 SDCM

Photometric Performance



83W 5200 lumen
• LOR = 100%

To Specify

IP65 LED post top lantern with ultra slim circular die cast aluminium body and integrated cooling fins. With wide symmetrical distribution having zero upward light. Electronic control gear with voltage surge protection and double insulated safety switch – as Whitecroft Lighting SIROCCO DISC.