

broadwalk line recessed

Wall mounted recessed
LED luminaire for
outdoor applications



Optics

- Light output options:
 - 53 lumens (3200K – 3W)
 - 67 lumens (6300K – 3W)
- Forward throw downward distribution
- Zero light pollution

Body

- Die cast aluminium
- UV stabilised nylon mounting box
- Coated for humidity and UV resistance
- IP65 IK08 rated protection
- Supplied with IP65 rated cable glands
- Finished in Silver
- Suitable for ambient temperatures between -20°C to +40°C



Order Codes

Broadwalk Line Recessed


3200K 53 lumens (3W)

6300K 67 lumens (3W)

BLR13KS

BLR16KS

Dimensions




L	W	H	KG
98	72	224	0.4

LED Performance

Colour Temp	Ra (CRI)	Life Expectancy	Colour Consistency
3200K	≥ 80	L ₇₀ (60,000hrs)	MacAdam 4 SDCM
6300K	≥ 80	L ₇₀ (60,000hrs)	MacAdam 4 SDCM

Photometric Performance



3W 67 lumen
• LOR = 100%

To Specify

IP65 Wall mounted recessed LED luminaire with die cast aluminium body. With forward throw downward distribution having zero upward light – as Whitecroft Lighting BROADWALK LINE RECESSED.