centurion PP65

IP65 perimeter security lighting bulkhead

EM IP 65

Optics

- Lamp options:
  - 26W TC-D (4000K)
  - 42W TC-T (4000K)
  - 70W SON-E (1900K)
  - 70W HQI-E (3000K)

Body

- IP65
- Black polycarbonate base and visor
- Clear UV stabilised prismatic polycarbonate diffuser
- Two 20mm dia knock-out options for the cable entry gland either side of the base
- Integral photocell option
- Integral emergency options on 26W – TC-D only (may not achieve design output at low ambient temperatures)
- Ambient operating temperature ranges:
  - Non Emergency, -30°C to +25°C
  - Emergency, -5°C to + 25°C
- Optional uplight controller to limit upward light ratio to 11%

Order Codes

Centurion PP65	Standard	Photocell
HQI-E 70W	CENP70H	CENP70HP
SON-E 70W	CENP70S	CENP70SP
TC-T 42W	CENP42	CENP42P
TC-D 26W	CENP26	CENP26P
TC-D 26W Emergency	CENP26EMIN	CENP26PEMIN
TC-D 26W COMEPS	CENP26/EP	CENP26P/EP

Options

UPLIGHT CONTROLLER* Add suffix **/UC** i.e. CENP70H**/UC**

* Not available for SON-E versions

Dimensions



L	H	W	KG	KG EM
260	290	192	2.0	3.0

Lamp Performance

Wattage	IL@25°C	Lamp Life	Ra(CRI)
26W TC-D	1800	13,000hrs	Ra 82
42W TC-T	3200	13,000hrs	Ra 82
70W SON-E	5810	28,500hrs	Ra 25
70W HQI-E	5000	12,500hrs	Ra 80

Photometric Performance

1 x 42W TC-T
• LOR = 78%

To Specify

IP65 perimeter security lighting bulkhead suitable for direct surface mounting with a 4 point fixing employing two key slots and 2 locking screws and timed ignitor on SON versions. Black polycarbonate base and visor and UV stabilised prismatic polycarbonate diffuser. Fluorescent and HID lamp options – as Whitecroft Lighting CENTURION PP65