

# centurion PP65 LED

IP65 perimeter security  
LED lighting bulkhead



## Optics

- Light Output Options:
  - 1239 lumens, 16W
  - 3200 lumens, 39W

## Body

- IP65
- DALI as standard
- 4000K
- Black polycarbonate visor and die-cast aluminium base
- Clear UV stabilised prismatic polycarbonate diffuser with Miro 5 reflector mounted internally
- Two 20mm diameter knock-out options for cable entry gland at either side of the base
- Ambient operating temperature ranges:
  - Non Emergency, -30°C to +25°C
  - Emergency, -5°C to + 25°C
- Integral emergency options in standard 3hr, Easytest and COMECS




## Order Codes

Centurion PP65 LED	DALI	3hr Emergency
1239 lumen, 16W	CENPL0Y	CENPL0YEM
3200 lumen, 39W	CENPL1Y	CENPL1YEM

## Options

EASYTEST	Add suffix /ET	i.e. CENPL1Y/ET
COMECS	Add suffix /EP	i.e. CENPL1Y/EP

## Dimensions



L	D	H	KG	KG
350	212	330	6.2	6.6


## LED Performance

Colour Temp	Ra (CRI)	Life Expectancy	Colour Consistency
4000K	≥ 80	L <sub>80</sub> (50,000hrs)	MacAdam 5 SDCM

## Equivalent Lamp Types

1239 lumens	TC-D 26W
3200 lumens	SON-E 70W

## Photometric Performance



39W 3200 lumen  
4000K  
• LOR = 100%  
• SHR MAX = 1.28

## To Specify

IP65 perimeter security LED lighting bulkhead suitable for direct surface mounting with a 4 point fixing employing two key slots and 2 locking screws. Black polycarbonate visor and die-cast aluminium base with UV stabilised prismatic polycarbonate diffuser and Miro 5 reflector – as Whitecroft Lighting CENTURION PP65 LED.