

# mirage LED IP65

Ceiling recessed LED luminaire  
for outdoor applications



## Optics

- Light output options:
  - 1645 lumens (24W) Clear diffuser
  - 1629 lumens (24W) Acrylic feature glass
- Wide beam symmetrical distribution
- Clear flat acrylic diffuser in bezel or acrylic feature optic
- Anodised aluminium reflector

## Body

- Extruded and cast aluminium
- IP65 IK10 rated protection
- Finished in Anthracite Grey
- To suit ceiling thickness 5 – 50mm



Acrylic feature glass

## Order Codes

### Mirage LED IP65

1645 lumen (24W)  
1629 lumen (24W)

Clear diffuser  
Acrylic feature glass

**M65AH164K**  
**M65BH164K**


### Options

DALI DIMMING  
3000K

Replace H with **Y**  
Replace 4 with **3**

i.e. M65AY164K  
i.e. M65AH163K

## Dimensions




Ø	H	L	CAØ	KG
202	132	174	185	2.8

## LED Performance

Colour Temp	Ra (CRI)	Life Expectancy	Colour Consistency
4000K	≥ 80	L <sub>70</sub> (50,000hrs)	MacAdam 3 SDCM

## Photometric Performance



24W 1645 lumen  
• LOR = 100%

## To Specify

IP65 Recessed LED luminaire with aluminium body and clear diffuser or part screened feature optic. With wide beam distribution – as Whitecroft Lighting MIRAGE LED IP65.