

spectre SL

Surface ceiling mounted cylindrical LED luminaire for outdoor applications



Optics

- Light output options:
 - 1645 lumens (24W) - Clear diffuser
 - 1629 lumens (24W) - Acrylic feature glass
- Wide beam symmetrical distribution
- Zero light pollution
- Clear flat acrylic diffuser in bezel or acrylic feature optic
- Anodised aluminium reflector

Body

- Extruded anodised aluminium
- IP65 IK10 rated protection
- Finished in Anthracite Grey
- Suitable for ambient temperatures between -20°C to +40°C

Order Codes

Spectre SL

1645 Lumen (24W) Clear diffuser
1629 Lumen (24W) Acrylic feature glass

SPLAH164K
SPLBH164K


Options

DALI DIMMING	Replace H with Y	i.e. SPLAH164K
3000K	Replace 4 with 3	i.e. SPLAH163K



Acrylic feature glass


Dimensions



LED Performance

Colour Temp 4000K	Ra (CRI) ≥ 80	Life Expectancy L ₇₀ (50,000hrs)	Colour Consistency MacAdam 4 SDCM
----------------------	------------------	--	--------------------------------------

Photometric Performance



Clear diffuser
24W 1645 lumen
• LOR = 100%

To Specify

IP65 Surface ceiling mounted cylindrical LED luminaire with extruded aluminium body and clear diffuser or part screened feature optic. With downward distribution having zero upward light – as Whitecroft Lighting SPECTRE SL.