


Leclanché Capacitors
48, av. de Grandson
1400 Yverdon, Switzerland



Tel. +41 24 445 66 88
Fax +41 24 445 66 89
capinfo@Lcap.ch
www.Lcap.ch

Drawing No. : 1027308-53567
created from : 05/06/2014 13:59:00

Part Number : AG15110016030



∅ D : 16 mm
L : 30 mm
l : 40 mm
d : 0,8 mm

Terminals : Wire

Electrical Parameter

| | | |
|--|--------------------|--------------------|
| Rated Capacitance (C _R) @ 100 Hz / 20 °C | 150 μF | |
| Tolerance | ±20 % | |
| Rated Voltage (U _R) | 100 V | |
| Surge Voltage (U _S) max. 5 x 1 min / h | 115 V | |
| Reverse Voltage (U _U) max. 1 s | 2 V | |
| Leakage Current (I _L) @ U _R / 5 min / 20 °C | 45 μA | |
| ESR typ. @ 100 Hz / 20°C | 389 mΩ | |
| Tan δ typ. @ 100 Hz / 20°C | 11 % | |
| Z max. @ 10 kHz / 20°C | 311 mΩ | |
| ESL typ. | 20 nH | |
| Rated Ripple Current (I _R) @ 100 Hz / 125 °C | 0,7 A | |
| Useful life @ I _R , U _R , 125 °C | 2000 h | |
| IEC Climatic category / Standards | 55/125/56 | IEC 60384-4 |
| Applications | General Industrial | |
| Your article No. / Project | | |