

Leclanché Capacitors
48, av. de Grandson
1400 Yverdon, Switzerland




Tel. +41 24 445 66 88
Fax +41 24 445 66 89
e-mail: <mailto:capinfo@lcap.ch>
www.lcap.ch

Customer : Leclanché Capacitors Sarl
Drawing No. : PA11501417
06.06.12

page 1 / 1

Typ : AG33104012030

RoHS Compliant



Ø D : 12 mm
L : 30 mm
l : 40 mm
d : 0,8 mm

Terminals : Wire

Electrical Parameter

Rated Capacitance (C_R) 100 Hz / 20 °C	330 μ F	
Tolerance	±20 %	
Rated Voltage (U_R)	40 V	
Surge Voltage (U_S) max. 5 x 1 min / h	46 V	
Reverse Voltage (U_U) max. 1 s	2 V	
Leakage Current (I_L) U_R / 5 min / 20 °C	79 μ A	
ESR typ. 100 Hz / 20°C	241 m Ω	
Tan δ typ. 100 Hz / 20°C	5 %	
Z max. 10 kHz / 20°C	193 m Ω	
ESL typ.	20 nH	
Rated Ripple Current (I_R) 100 Hz / 125°C	0,7 A	
Useful Life @ I_R , U_R , 125°C	2000 h	
IEC Climatic category / Standards	55/125/56	IEC 60384 - 4
Applications	Industrial	
Your article No. / Project		