

Leclanché Capacitors  
48, av. de Grandson  
1400 Yverdon, Switzerland



Tel. +41 24 445 66 88  
Fax +41 24 445 66 89  
[capinfo@Lcap.ch](mailto:capinfo@Lcap.ch)  
[www.Lcap.ch](http://www.Lcap.ch)

Drawing No. : Preliminary ...1026115  
created from : 09/07/2014 16:03:00

**Part Number : Cuboid Cap CC22206316035035**

	<p>l : 35 mm B : 16 mm H : 35 mm a : 10 mm : Terminals : Wire 0,8mm</p>	<p>Sealing  Laser welded Al with  Teflon gaskets</p>
--	---	--

**Electrical Parameter**

Rated Capacitance ( $C_R$ ) @ 100 Hz / 20 °C	<b>2200</b> $\mu$ F	
Tolerance	<b><math>\pm 20</math></b> %	
Rated Voltage ( $U_R$ )	<b>63</b> V	
Surge Voltage ( $U_S$ ) max. 5 x 1 min / h	<b>72</b> V	
Reverse Voltage ( $U_U$ ) max. 1 s	<b>2</b> V	
Leakage Current ( $I_L$ ) @ $U_R$ / 5 min / 20 °C	<b>830</b> $\mu$ A	
ESR typ. @ 100 Hz / 20°C	<b>72</b> m $\Omega$	TBD in Measurement
Tan $\delta$ typ. @ 100 Hz / 20°C	<b>10</b> %	TBD in Measurement
Z max. @ 10 kHz / 20°C	<b>58</b> m $\Omega$	TBD in Measurement
ESL typ.	<b>20</b> nH	
Rated Ripple Current ( $I_R$ ) @ 100 Hz / 125 °C	<b>2</b> A	TBD in Measurement
Useful life @ $I_R$ , $U_R$ , 125 °C	<b>10000</b> h	
IEC Climatic category / Standards	<b>40/125/56</b>	<b>IEC 60384-4</b> <b>Storage at -55°C possible</b>
Applications	Military	
Your article No. / Project		