

Leclanché Capacitors
48, av. de Grandson
1400 Yverdon, Switzerland



Tel. +41 24 445 66 88
Fax +41 24 445 66 89
capinfo@Lcap.ch
www.Lcap.ch

Drawing No. : Preliminary
created from : 26/09/2014 15:03:00

Part Number : CC561300134576

	<p>I : 45 mm B : 13 mm H : 76 mm a* 10/25 mm</p> <p>*Pitch to : be discussed</p> <p>Terminals : Wire 0,8mm</p>	<p>Sealing</p> <p>Laser welded Al with</p> <p>Teflon gaskets</p>
--	--	--

Electrical Parameter

Rated Capacitance (C _R) @ 100 Hz / 20 °C	560 μF	
Tolerance	±20 %	
Rated Voltage (U _R)	300 V	
Surge Voltage (U _S) max. 5 x 1 min / h	345 V	
Reverse Voltage (U _U) max. 1 s	2 V	
Leakage Current (I _L) @ U _R / 5 min / 20 °C	1000 μA	
ESR typ. @ 100 Hz / 20°C	166 mΩ	TBD in Measurement
Tan δ typ. @ 100 Hz / 20°C	6 %	TBD in Measurement
Z max. @ 10 kHz / 20°C	133 mΩ	TBD in Measurement
ESL typ.	20 nH	
Rated Ripple Current (I _R) @ 100 Hz / 85 °C	3,2 A	TBD in Measurement
Shock / Vibration Resistance		Shocks (50 g, pulse 11 ms, 18 shocks) / Vibration (10 to 500 Hz, 20g, 10 cycles)
Useful life @ I _R , U _R , 85 °C	10000 h	

Leclanché Capacitors
48, av. de Grandson
1400 Yverdon, Switzerland



Tel. +41 24 445 66 88
Fax +41 24 445 66 89
capinfo@Lcap.ch
www.Lcap.ch

Drawing No. : Preliminary
created from : 26/09/2014 15:03:00

Part Number : CC561300134576

IEC Climatic category / Standards	55/085/56	IEC 60384-4
Applications		
Your article No. / Project		
MTBF	2 x 10 ⁸ h	