

Leclanché Capacitors
48, av. de Grandson
1400 Yverdon, Switzerland



Tel. +41 24 445 66 88
Fax +41 24 445 66 89
capinfo@Lcap.ch
www.Lcap.ch

Drawing No. : 1026900-53567

created from : 11/04/2014 14:32:00 release: 11.04.2014 14:35

Part Number : GGA33125035080

	<p> $\varnothing D$: 35 mm L : 80 mm a : 13 mm h : 6 mm Safety valve : Silicon (8 bar) Terminals : M5 Isolation: Polyolefine </p>	
--	---	--

Electrical Parameter

Rated Capacitance (C_R) @ 100 Hz / 20 °C	330 μ F	
Tolerance	-10 +30 %	
Rated Voltage (U_R)	250 V	
Surge Voltage (U_S) max. 5 x 1 min / h	300 V	
Reverse Voltage (U_U) max. 1 s	2 V	
Leakage Current (I_L) @ U_R / 5 min / 20 °C	160 μ A	
ESR typ. @ 100 Hz / 20°C	290 m Ω	
Tan δ typ. @ 100 Hz / 20°C	6 %	
Z max. @ 10 kHz / 20°C	230 m Ω	
ESL typ.	20 nH	
Rated Ripple Current (I_R) @ 100 Hz / 125 °C	2,8 A	
Useful life @ $I_R, U_R, 125$ °C	4000 h	15000h @ 105°C
IEC Climatic category / Standards	55/125/56	IEC 60384-4
Applications	General Industrial	
Your article No. / Project		