

Leclanché Capacitors
48, av. de Grandson
1400 Yverdon, Switzerland



Tel. +41 24 445 66 88
Fax +41 24 445 66 89
capinfo@Lcap.ch
www.Lcap.ch

Drawing No. : 1015794-53567
created from : 06/05/2014 10:16:00

Part Number : SIH47145035050

	$\varnothing D$: 35 mm L : 50 mm h : 6,3 mm	
	Insulation : PVC 2500 Vac Terminals : Snap In	

Electrical Parameter

Rated Capacitance (C_R) @ 100 Hz / 20 °C	470 μ F	
Tolerance	± 10 %	
Rated Voltage (U_R)	450 V	
Surge Voltage (U_S) max. 5 x 1 min / h	495 V	
Reverse Voltage (U_U) max. 1 s	2 V	
Leakage Current (I_L) @ U_R / 5 min / 20 °C	1270 μ A	
ESR typ. @ 100 Hz / 20°C	203 m Ω	
Tan δ typ. @ 100 Hz / 20°C	6 %	
Z max. @ 10 kHz / 20°C	163 m Ω	
ESL typ.	20 nH	
Rated Ripple Current (I_R) @ 100 Hz / 105 °C	1,7 A	
Useful life @ $I_R, U_R, 105$ °C	5000 h	
IEC Climatic category / Standards	40/105/56	IEC 60384-4
Applications	General Industrial	
Your article No. / Project		