

#6286



HIGH VOLTAGE METALLIZED CAPACITORS

PPMHT 1200-110 d K

Dielectric
metallized polypropylene

Polyester wrapped

Epoxy resin sealing



Parameter	Symbol		Value	Unit	Condition
Capacitance	C		10	nF	1 V / 1 kHz
Tolerance			± 10	%	
Rated voltage	Un DC		12000	VDC	
Rated voltage	Un AC		500	Veff	50 Hz
slope of voltage variation	du/dt max.		3'000	V/µsec	max. repetitive
RMS current	I RMS max.		0.7	Aeff	50 kHz
Tangent delta	tgδ		< 7	10 ⁻⁴	1 V / 1 kHz
Stray inductance	ESL		≤ 50	nH	
Insulation resistance	Ri		>100'000	MΩ	500 VDC - 1 min
Test voltage between terminals	U T1		18'000	VDC	10 s
Operating temp.			- 40 / + 85 °C		
Estimated operational life (-3%)			90000	h	Un DC / 65°C
Dimension	Symbol			Unit	Conditions
Diameter	D		16	mm	
Lenght	L		60	mm	
Terminals					
Axial tinned wire	d		1.0	mm	
	M1				
	M0				
	Modification	Date	Visa émetteur		

Condensateurs CH 1400 Yverdon, Switzerland
 Kondensatoren Tel.: ++41 24 445 66 88
 Capacitors Fax: ++41 24 445 66 89

Leclanché
Capacitors
A FISCHER & TASSCHÉ COMPANY

HJJ

www.Lcap.ch
 10.04.2014

capinfo@Lcap.ch
 faisab6286.XLS