


#6188

METALLIZED POLYESTER CAPACITORS

MKT 25-256 ga K



Dielectric of metallized polyester

Self-extinguishing plastic housing / Epoxy resin sealing

Parameter	Symbol		Value	Unit	Condition
Capacitance	C		5.6	nF	1 V / 1 kHz
Tolerance			± 10	%	
Rated voltage	Un DC	85°C	250	VDC	
Rated voltage	Un AC	75°C	160	VAC	50 Hz
slope of voltage variation	du/dt max.		71	V/ μ sec	max. repetitive
Repetitive surge current	I cr. max		0.4	A	
Tangent delta	tg δ		7C	1C ⁴	1 V / 1 kHz
Stray inductance	ESL		≤ 30	nH	
Insulation resistance	Ri		> 30'000	M Ω	100 VDC - 1 min
Test voltage between terminals	U T1		400	VDC	10 s
Operating temperature			- 40 / + 100	°C	
Estimated operational life (-3%)			100'000	h	Un DC - 70°C
Dimension	Symbol			Unit	Conditions
Width	B		4	mm	
Height	H		9	mm	
Length	L		10	mm	
Terminals					
Axial tinned wire	d		$\varnothing 0.6 \times 20$	mm	
	RM		7.62	mm	
	M1				
	M0				
	Modification	Date	Visa émetteur		

Condensateurs CH 1400 Yverdon, Switzerland
 Kondensatoren Tel.: ++41 24 445 66 88
 Capacitors Fax: ++41 24 445 66 89

Leclanché
Capacitors
A FISCHER & TAUSSIG COMPANY

HJJ

www.Lcap.ch
 27.05.2013

capinfo@Lcap.ch
 faisab6188.XLS