



#5916

METALLIZED POLYPROPYLENE CAPACITORS

PPM 200-133 g K



Dielectric of metallized polypropylene

Self-extinguishing plastic housing / Epoxy resin sealing UL-V0

Parameter	Symbol	Value	Unit	Condition
Capacitance	C	33	nF	1 V / 1 kHz
Tolerance		± 10	%	
Rated voltage	Un DC	2000	VDC	
Rated voltage	Un AC	850	VAC	
slope of voltage variation	du/dt max.	1000	V/ μ sec	max. repetitive
Repetitive surge current	I cr. max	33	A	
Tangent delta	tg δ	4	10^{-4}	1 V / 1 kHz
Tangent delta	tg δ	4	10^{-4}	1 V / 10 kHz
Stray inductance	ESL	≤ 30	nH	
Insulation resistance	Ri	> 100'000	M Ω	500 VDC - 1 min
Test voltage between terminals	U T1	3200	VDC	10 s.
Climatic category		40/85/56		
Dimension	Symbol	Value	Unit	Conditions
Width	B	14	mm	
Height	H	24	mm	
Length	L	31.5	mm	
Terminals				
Axial tinned wire	d	$\phi 0.8 \times 25$	mm	
	RM	27.5 ± 0.5	mm	
	M1			
	M0			
	Modification	Date	Visa émetteur	

Condensateurs CH 1400 Yverdon, Switzerland
 Kondensatoren Tel.: ++41 24 445 66 88
 Capacitors Fax: ++41 24 445 66 89

Le Janché
Capacitors
A FENICHER & TAGSCHER COMPANY

HJJ

www.Lcap.ch
 12.04.2010

capinfo@Lcap.ch
 faisab5916.XLS