

Technical data

Nominal capacitance	C_N	135 $\mu\text{F} \pm 10\%$
Nominal voltage dc	U_{NDC}	900 V
AC voltage max	U_{MaxAC}	125 V
Energy	W_N	54,7 Ws
Max. current /1 kHz @ Busbar Temp < 50 °C	I_{Max}	100 A

Max. periodic Peak current	$\hat{I}_{\text{Periodic}}$	2700 A
Max. Pulse rise time	$\Delta U/\Delta t$	20 V/ μs
Series resistance	R_{ESR}	< 1 m Ω
Dissipation factor	$\tan\delta$	8,7 $\times 10^{-4}$
Therm. Resistant to Busbar	R_{th}	3,1 K/W

Self inductance	L_E	10,5 nH
-----------------	-------	---------

Min. Operating temperature	ϑ_{min}	-25 °C
Max. Operating temperature	ϑ_{max}	+70 °C
Storage temperature	ϑ_{Lager}	-40...+85 °C

Climatic category DIN IEC 68/1	25/070/21
--------------------------------	-----------

Test Data

Test voltage between terminals	U_{TT}	1350 V dc / 10s
--------------------------------	-----------------	-----------------

Life expectancy	100000 h
@ hot spot	60 °C
Failure rate	FIT 100

General technical data

Coating	PA 66 plastic case with polyurethane resin sealing Flame retardant UL 94V-0 compliant
Dielectric	Polypropylene
Terminals	Nickel-plated brass inserts M5 x 7,5 mm
Torque M8	6 Nm
Creepage distance	29 mm
Weight	~ 0,4 kg

