





#5812

Power Electronics Capacitors

MKT 10-8.2 SMD M

PRELIMINARY



Surface mount device - Self-extinguishing plastic housing
Dielectric metallized polyester - Epoxy resin sealing UL 94-V0

Parameter	Symbol		Value	Unit	Condition
Capacitance	C		8.2	μF	1 V / 1 kHz
Tolerance			± 20	%	
Rated voltage	Un DC		100	VDC	
Rated voltage	Un AC		30	Veff	50 Hz
RMS current	I RMS max.		5.6	Aeff	300 kHz / 105 °C
Tangent delta	tg δ		≤ 90	1C^4	1 kHz
Equivalent serie resistance	ESR		≤ 5.4	m Ω	300 kHz
Stray inductance	ESL		≤ 5	nH	
Insulation resistance	Ri		> 152	M Ω	100 VDC - 1 min
Test voltage between terminals	U T1		160	VDC	10 s
Climatic category			55/125/21		
Dimension	Symbol			Unit	Conditions
Width	B max		17	mm	
Height	H max		10	mm	
Length	L max		18.5	mm	
Terminals					
	R		2.25 ± 0.25	mm	
	S		2 ± 0.2	mm	
	T		7.0 ± 0.2	mm	
	M1				
	M0				
	Modification	Date	Visa émetteur		

Condensateurs CH 1400 Yverdon-les-Bains
Kondensatoren Tel.: ++41 24 445 66 88
Capacitors Fax: ++41 24 445 66 89

Le lancé
Capacitors
A FISCHER & TASESCHE COMPANY

HJJ

30.04.2009

faisab5812.XLS