





#5860

Power Electronics Capacitors

MKT-4 5-50.0 a K

Operating conditions
90 °C

Frequency [kHz]	Current I RMS max
50	14.0 A
75	13.3 A
100	12.5 A

Dielectric : metallized polyester
Polyester wrapped, Flammibility UL 510
Epoxy resin sealing UL 94-V0

Parameter	Symbol		Value	Unit	Condition
Capacitance	C		50	μF	1 V / 1 kHz
Tolerance			± 10	%	
Rated voltage	Un DC		50	VDC	100 °C
Rated voltage	Un AC		24	Veff	50 Hz
Tangent delta	tgδ		≤ 85	10 ⁻⁴	1 kHz
Equivalent serie resistance	ESR		≤ 3.0	mΩ	50 kHz
Stray inductance	ESL		≤ 15	nH	
Insulation resistance	Ri		400	MΩ	50 VDC - 1 min
Test voltage between terminals	U T1		80	VDC	10 s
Operating temperature			- 55 / + 125 °C		
Dimension	Symbol			Unit	Conditions
Width	B		20.5	mm	
Height	H		12.5	mm	
Length	L		26.5	mm	
Terminals					
Radial tinned wire	ø		0.8	mm	
RM1			7.5 ± 0.7	mm	
RM2			22.5 ± 0.7	mm	
	M1				
	M0				
	Modification	Date	Visa émetteur		

Condensateurs CH 1400 Yverdon-les-Bains
Kondensatoren Tel.: ++41 24 445 66 88
Capacitors Fax: ++41 24 445 66 89

Le Janché
Capacitors
A FISCHER & KAUZSCHE COMPANY

HJJ

24.09.2009

faisab5860.XLS