

Leclanché Capacitors
48, av. de Grandson
1400 Yverdon, Switzerland



Tel. +41 24 445 66 88
Fax +41 24 445 66 89
capinfo@Lcap.ch
www.Lcap.ch

Drawing No. : 1026731-53154
created from : 14/02/2014 15:14:00

Part Number : SI4P33236035125

	<p>∅ D : 35 mm L : 125 mm h : 4,5 mm</p>	<p>Drill plan</p>
<p>Insulation : PVC 2500 Vac Terminals : Snap In</p>		<p>NC terminals could be connected to the electrical circuit!</p>

Electrical Parameter

Rated Capacitance (C_R) @ 100 Hz / 20 °C	3300 μ F	
Tolerance	±10 %	
Rated Voltage (U_R)	360 V	
Surge Voltage (U_S) max. 5 x 1 min / h	375 V	
Reverse Voltage (U_U) max. 1 s	2 V	
Leakage Current (I_L) @ U_R / 5 min / 20 °C	7128 μ A	
ESR typ. @ 100 Hz / 20°C	29 m Ω	
Tan δ typ. @ 100 Hz / 20°C	6 %	
Z max. @ 10 kHz / 20°C	23 m Ω	
ESL typ.	20 nH	
No of flashes	10 Mio h	
IEC Climatic category / Standards	40/60/56	IEC 60384-4
Applications	Flash	
Your article No. / Project		