

Features:

- Universal / Full range AC input
- Fitted with 2.1 DC jack plug
- UK, Euro, US & Australian Interchangeable AC head.
- Class II power (no earth)
- Small & Compact design
- Protections: Over Voltage, Over Current & Short Circuit
- Level V ErP/EuP efficiency compliant



Output Characteristics

Part Number	T5588ST
Voltage	+12Vdc
Current Max.	4A
Current Min.	0A
Power (watts)	48W
Line Regulation	+/- 1%
Hold-up Time	10 Seconds Minimum
Ripple & Noise (mV p-p)	120mVp-p (max)
Protections	Over Voltage, Over Current & Short Circuit
Output Cord	1500mm Jack Plug (5.5mm X 2.1mm X 12mm)

Input Characteristics

Rated Input Voltage	100 - 240Vac
Full Input Voltage Range	90 - 264Vac
Rated Frequency	50/60Hz
Full Frequency Range	47-63Hz
Efficiency (min.)	84%
Input Current (RMS Max.)	1.3A
AC Inrush Current	30A

Safety, Mechanical and Other Characteristics

Range Model Designations	ICP48-120-4000
Operating Temperature	-20°C to 40°C
Storage Temperature	-20°C to 75°C
Operating Humidity	20 - 90%
Storage Humidity	0 - 90%
Safety Standards	UL (UL60950), FCC (Part 15 CLASS B), CE (EN60950/EN55022), GS (EN60950/EN55022), SAA (AS/NZS60950.1: 2011)
Case Size (LxWxH)	97.3mm X 39.4mm X 45.3mm

Drawings:

