



230Vac : 24Vac Wall Mount PSU Range

43AV & 72VA

Safety Certifications



Electrical Specifications

Information	Part No.	T3445SA	T3867SA	T3868SA
	Model No.	AC-2400750	AC-2402000	AC-2403000

Output	Voltage	24 VAC	24 VAC	24Vac
	Current (max)	750mA	2A	3A
	Volts (No Load)	26.6VAC	26.6VAC	27VAC

Environment	Operating Temp.	0 to 40°C	0 to 40°C	0 to 40°C
	Storage Temp.	-20 to 70 °C	-20 to 70 °C	-20 to 70 °C
	Temperature Rise	80°C Max	80°C Max	80°C Max

Input	Voltage Range	230VAC	230VAC	230VAC
	Frequency	50Hz	50Hz	50Hz
	Magnetising Current (max.)	60mA	60mA	100mA

Other	Output Connector	Bare Ended	Bare Ended	Bare Ended
	Lead Length	2 & 1.8Mtr	2 & 1.8Mtr	2 & 1.8Mtr
	Case Length	97mm	97mm	97mm
	Depth	73mm	73mm	73mm
	Width	29mm	29mm	29mm
	Unit's Weight	1.1Kg	1.1Kg	1.1Kg
	Wareproof	No	No	Yes - to IP67

Safety & EMC	Hi Pot Test I/P-O/P	3.75KVac 1 Minute	3.75KVac 1 Minute	3.75KVac 1 Minute
	Insulation I/P-O/P	100Mohm	100Mohm	100Mohm
	Certification	CE		

Schematic

