



24Volt AC Waterproof PSU Range

- Universal AC Input 90—264Vac
- Low ripple & noise
- No minimum load requirement
- 100% burn in test
- 1 year warranty
- Safety: CE
- Water Resistant Case
- Wall Mountable
- IP66 Rating

Information	Part No.	T4215AD	T4459AD	T4468AD	T4033AD
-------------	----------	---------	---------	---------	---------

Output	Voltage	24VAC	24VAC	24VAC	24VAC
	Current (Max)	1A	2A	3A	4A
	Current (Min)	0A	0A	0A	0A
	Load Regulation	+/-5%	+/-5%	+/-5%	+/-5%
	Over-Voltage Protection	N/A	N/A	N/A	N/A
	Over-Current Protection	1.0A Q/B	2.0A Q/B	3.0A Q/B	4.0A Q/B

Environment	Operating Temp.	0 to 40°C	0 to 40°C	0 to 40°C	0 to 40°C
	Storage Temp.	-20 to 70 'C	-20 to 70 'C	-20 to 70 'C	-20 to 70 'C
	Operating Humidity	35% to 85% Non-Condensing	35% to 85% Non-Condensing	35% to 85% Non-Condensing	35% to 85% Non-Condensing
	Storage Humidity	5 to 95% RH Non-condensing	5 to 95% RH Non-condensing	5 to 95% RH Non-condensing	5 to 95% RH Non-condensing

Input	Voltage Range	230VAC	230VAC	230VAC	230VAC
	Frequency	50Hz	50Hz	50Hz	50Hz
	Current RMS (Max)	155mA	155mA	155mA	155mA
	Magnetising Current	65mA	65mA	65mA	65mA
	Leakage Current	>0.25mA	>0.25mA	>0.25mA	>0.25mA

Other	Efficiency	80%	80%	80%	80%
	MTBF	50K Hours	50K Hours	50K Hours	50K Hours
	Dimensions	140 x 80 x 85 mm	140 x 80 x 85 mm	140 x 80 x 85 mm	140 x 80 x 85 mm
	No-Load Power Consumption	0.5W max	0.5W max	0.5W max	0.5W max

Safety & EMC	Hi Pot Test I/ P-O/ P	3.75KVAC	3.75KVAC	3.75KVAC	3.75KVAC
	Insulation I/ P-O/ P	500Mohm	500Mohm	500Mohm	500Mohm
	Certification	Low Voltage Directive 73/23/EEC (including 93/68/EEC)			
		EMC Directive 89/336/EEC (including 92/31/EEC & 93/68/EEC)			



Weight:
525g
Approx.

Dimensions
(in mm):

