

LV Range - Constant Voltage IP67 LED Drivers



Features:

- Constant Voltage Driver
- Universal AC Input
- Fully encapsulated to IP67
- Protections: Short Circuit / Over Current
- Small and attractive black case
- Wall Mountable
- 2 Year Warranty

Compliance:

- Magnetic Emissions: EN55015
- Harmonic: EN61000-3-2
- Immunity: EN61547
- Safety: EN61347-1, EN61347-2-13



Model	Input	Output	Ripple & Noise (Max.)	Efficiency (full load)	Dimensions (LxWxH)
LV5-12	100-240Vac	12Vdc 0.4A	200mVp-p	≥76%	58x28x22mm
LV5-24	100-240Vac	24Vdc 0.2A	200mVp-p	≥78%	58x28x22mm
LV12-12	100-240Vac	12Vdc 1A	300mVp-p	≥76%	130x25x21mm
LV12-24	100-240Vac	24Vdc 0.5A	300mVp-p	≥80%	130x25x21mm
LV20-12	100-240Vac	12Vdc 2A	300mVp-p	≥80%	140x30x20mm
LV20-24	100-240Vac	24Vdc 1A	300mVp-p	≥82%	140x30x20mm
LV35-12	100-240Vac	12Vdc 3A	300mVp-p	≥82%	148x32x26mm
LV35-24	100-240Vac	24Vdc 1.5A	300mVp-p	≥85%	148x32x26mm
LV50-12	100-240Vac	12Vdc 4A	300mVp-p	≥84%	148x40x30mm
LV50-24	100-240Vac	24Vdc 2A	300mVp-p	≥87%	148x40x30mm
LV60-12	100-240Vac	12Vdc 5A	300mVp-p	≥84%	162x42.5x30mm
LV60-24	100-240Vac	24Vdc 2.5A	300mVp-p	≥87%	162x42.5x30mm
LV75-12	100-240Vac	12Vdc 6.5A	300mVp-p	≥84%	162x42.5x30mm
LV75-24	100-240Vac	24Vdc 3.25A	300mVp-p	≥86%	162x42.5x30mm

NEW: LV100E also available. Contact us for more information.