

LA-Y Range - Constant Current IP67 LED Drivers with PFC



Features:

- Constant Current Driver
- Universal AC Input
- Built-in active PFC function (PFC>0.85)
- Fully encapsulated to IP67
- Protections: Short Circuit / Over Current
- Small and attractive white case
- Wall Mountable
- 2 Year Warranty

Compliance:

- Magnetic Emissions: EN55015
- Harmonic: EN61000-3-2
- Immunity: EN61547
- Safety: EN61347-1, EN61347-2-13



Model	Input	Output	Suggested Loading	PFC	Efficiency (full load)	Dimensions (LxWxH)
LA12Y-350	100-240Vac	9-32Vdc 350mA	3---9 LED	≥0.85	≥85%	ø64x30mm
LA12Y-700	100-240Vac	3-16Vdc 700mA	1---4 LED	≥0.85	≥85%	ø64x30mm
LA20Y-350	100-240Vac	9-48Vdc 350mA	3---13 LED	≥0.85	≥85%	ø78x30mm
LA20Y-700	100-240Vac	3-28Vdc 700mA	1---8 LED	≥0.85	≥85%	ø78x30mm
LA35Y-350	100-240Vac	40-80Vdc 350mA	12---22 LED	≥0.9	≥90%	ø96x32mm
LA35Y-700	100-240Vac	24-48Vdc 700mA	7---13 LED	≥0.9	≥90%	ø96x32mm
LA35Y-1050	100-240Vac	15-30Vdc 1050mA	5---8 LED	≥0.9	≥90%	ø96x32mm
LA35Y-1400	100-240Vac	12-24Vdc 1400mA	4---6 LED	≥0.9	≥90%	ø96x32mm