

LA-P Range - Constant Current IP67 LED Drivers with PFC



Features:

- Constant Current Driver
- Universal AC Input
- Built-in active PFC function (PFC>0.9)
- Fully encapsulated to IP67
- Protections: Short Circuit / Over Current
- Small and attractive white case
- Wall Mountable
- 2 Year Warranty

Compliance:

- UL1310 Class 2 power unit, pass LPS
- Magnetic Emissions: EN55015
- Harmonic: EN61000-3-2
- Immunity: EN61547
- Safety: EN61347-1, EN61347-2-13



Compliant LA20P & LA35P Only

Model	Input	Output	Suggested Loading	Efficiency (full load)	Dimensions (LxWxH)
LA9P-350	100-240Vac	15-30Vdc 350mA	4---8 LED	≥78%	130x25x21mm
LA9P-700	100-240Vac	8-15Vdc 700mA	3---4 LED	≥75%	130x25x21mm
LA20P-350	100-240Vac	24-48Vdc 350mA	8---13 LED	≥82%	140x30x20mm
LA20P-700	100-240Vac	14-28Vdc 700mA	5---8 LED	≥82%	140x30x20mm
LA35P-350	100-240Vac	40-80Vdc 350mA	12---22 LED	≥87%	148x32x26mm
LA35P-700	100-240Vac	24-48Vdc 700mA	8---13 LED	≥85%	148x32x26mm
LA35-1050	100-240Vac	16-32Vdc 1050mA	5---18 LED	≥87%	148x32x26mm
LA35-1400	100-240Vac	12-24Vdc 1400mA	4---6 LED	≥85%	148x32x26mm
LA50P-700	100-240Vac	36-72Vdc 700mA	11---20 LED	≥87%	148x40x30mm
LA50P-1050	100-240Vac	24-48Vdc 1050mA	8---13 LED	≥87%	148x40x30mm
LA50P-1400	100-240Vac	18-36Vdc 1400mA	6---10 LED	≥87%	148x40x30mm
LA60P-700	100-240Vac	40-80Vdc 700mA	12---22 LED	≥88%	162x42.5x30mm
LA60-1050	100-240Vac	30-60Vdc 1050mA	9---16 LED	≥88%	162x42.5x30mm
LA60-1400	100-240Vac	20-42Vdc 1400mA	6---12 LED	≥88%	162x42.5x30mm
LA60-1750	100-240Vac	18-36Vdc 1750mA	6---10 LED	≥88%	162x42.5x30mm
LA60P-2100	100-240Vac	15-30Vdc 2100mA	5---8 LED	≥88%	162x42.5x30mm



Stontronics Ltd. Chancerygate Business Centre, Cradock Road, Reading, Berkshire, RG2 0AH.
 Tel: +44 (0) 118 931 1199 • Fax: +44 (0) 118 931 1145 • Email: info@stontronics.co.uk • Web: www.stontronics.co.uk

Please Note: Image shown is representative of entire range. Individual PSU image &/or drawings or data sheets available on request.
 Stontronics Ltd accepts no responsibility for typographical errors in the production of this leaflet. Product specifications are subject to change without notice.