

1.5A to 4A Desktop Charger Range

This range of Stontronics battery chargers are high quality UK manufactured intelligent systems. Designed for many applications including Leisure, fire & security, medical, automotive, mobility, industrial, golf, standby or cyclic.

Product Image



Features

- Microprocessor - controlled multistage charging
 - Charges all lead acid batteries
- Ability to charge batteries drained to a low voltage level
 - Fully automatic charging
 - Proportional charging
 - Soft start current control
 - Sulphated battery recovery
 - Over discharged battery recovery
- LED indication of short circuit, reverse polarity & open circuit
 - 1.8mt long output lead fitted with crocodile clips
 - Conforms to all the latest standards
 - 1 Year Warranty

Part Number and Output Table

Part No.	Current	Voltage	Voltage (float)	Voltage (bulk)	Input Voltage (& Optional)
SRE3A12	3Amp	12V	13.6V	14.5V	230Vac (110Vac)
SRE4A12	4Amp	12V	13.6V	14.5V	230Vac (110Vac)
SRE1.5A24	1.5Amp	24V	27.2V	29.0V	230Vac (110Vac)
SRE2A24	2Amp	24V	27.2V	29.0V	230Vac (110Vac)

Technical Specifications

Mains Input 230Vac (110Vac optional)
 Mains Input Range 207-258Vac 44-67Hz
 (optional 98-120Vac 44-67Hz)
 Operating Temp. -20 to +50°C free air cooled
 Humidity 75% NC
 Case Material Moulded plastic ABS case
 Dimensions 142 x 103 x 91mm (LxWxH)
 Weight 1.9Kg (approx.)

LED Indication

Constant red LED Bulk charge mode
 Constant Green LED Float charge mode
 Red flashing LED Trickle charge low battery detected
 Red & Green flashing LED Fault: No battery
 connected, battery reverse
 polarity or output short circuit

Disclaimer

Stontronics Ltd accepts no responsibility for typographical errors in the production of this leaflet. Product specifications are subject to change without notice.

For more information please contact us:

Stontronics Ltd,
 Chancerygate Business Centre, Cradock Road, Reading, Berkshire, RG2 0AH
 Tel: 0118 931 1199
 Fax: 0118 931 1145
 Email: info@stontronics.co.uk • www.stontronics.co.uk

Additional Options

- UK, Euro & USA lead and case also available upon request
- Output leads can be fitted with customer specific connectors